

# *Ultrafiltration based purification strategies for surfactin produced by bacillus subtilis lb5a using cassava wastewater as substrate*

Article

Accepted Version

De Andrade, C. J., Barros, F. F. C., De Andrade, L. M., Roco, S. A., Sforca, M. L., Pastore, G. M. and Jauregi, P. (2016) Ultrafiltration based purification strategies for surfactin produced by bacillus subtilis lb5a using cassava wastewater as substrate. *Journal of Chemical Technology and Biotechnology*, 91 (12). pp. 3018-3027. ISSN 1097-4660 doi: 10.1002/jctb.4928 Available at <https://centaur.reading.ac.uk/67256/>

It is advisable to refer to the publisher's version if you intend to cite from the work. See [Guidance on citing](#).

To link to this article DOI: <http://dx.doi.org/10.1002/jctb.4928>

Publisher: Wiley

All outputs in CentAUR are protected by Intellectual Property Rights law, including copyright law. Copyright and IPR is retained by the creators or other copyright holders. Terms and conditions for use of this material are defined in

the [End User Agreement](#).

[www.reading.ac.uk/centaur](http://www.reading.ac.uk/centaur)

## **CentAUR**

Central Archive at the University of Reading

Reading's research outputs online

**ULTRAFILTRATION BASED PURIFICATION STRATEGIES FOR  
SURFACTIN PRODUCED BY *Bacillus subtilis* LB5A USING CASSAVA  
WASTEWATER AS SUBSTRATE**

**Short title:** Ultrafiltration of surfactin produced using cassava wastewater

\*Cristiano José de Andrade<sup>1</sup>, Francisco Fábio Cavalcante Barros<sup>1</sup>, Lidianie Maria de Andrade<sup>2</sup>, Silvana Aparecida Rocco<sup>3</sup>, Mauricio Luis Sforça<sup>3</sup>, Gláucia Maria Pastore<sup>1</sup>, Paula Jauregi<sup>4</sup>

\*Corresponding author – [eng.crisja@gmail.com](mailto:eng.crisja@gmail.com), + 55 (19) 98154-3393, Present address: <sup>1</sup> Department of Food Science, Faculty of Food Engineering, State University of Campinas, P.O. Box 6121, 13083-862, Campinas, SP, Brazil; <sup>2</sup> Polytechnic School of the University of São Paulo, <sup>3</sup> Brazilian Bioscience National Laboratory, <sup>4</sup>University of Reading, Department of Food and Nutritional Science – Reading-UK.

**Abstract**

**BACKGROUND:** *Bacillus subtilis* synthesizes surfactin, a powerful surface-active agent. It has interesting potential applications. However, due to its high cost of production, commercial use is impracticable. The downstream processing represents  $\approx 60\%$  of production costs and the culture medium  $\approx 30\%$ . Many reports focused, separately, on production of surfactin using by-products (reduced cost) or the purification using synthetic medium. Therefore, the aim of this work was to evaluate, for the first time, the impact of using a by-product as fermentation medium on the downstream processing based on membrane filtration.

**RESULTS:** Membranes of PES-100-kDa efficiently retained surfactin micelles - the first step of ultrafiltration, whereas, the second step required membranes of 50-kDa to separate

surfactin monomers from proteins. Ultrafiltration of crude biosurfactant was associated with fouling and/or concentration polarization resulting in lower purity than when synthetic medium was used. Further improvement in purity was achieved by partial removal of proteins prior to ultrafiltration by precipitation and extraction. The RMN and MALDI-TOFMS analyses identified 11 potential surfactin homologous composed by two amino acid sequences.

CONCLUSION: Production of surfactin using cassava wastewater as a low-cost culture medium and its purification by the 2-step ultrafiltration process is feasible, nevertheless, the higher protein content of this medium as compared to the synthetic one leads to a lower purity product; further increase in purity can be achieved by applying additional purification steps prior to ultrafiltration with the subsequent increased in process cost.

Key terms: fermentation, purification, residues, ultrafiltration, wastewater.

## INTRODUCTION

A wide variety of microorganisms produce biosurfactants including *B. subtilis* that synthesizes lipopeptides such as surfactin, iturin, fengycin, etc. These compounds have high surface activity and resistance to extreme conditions.<sup>1-3</sup> They have raised a lot of interest due to their remarkable properties such as: high emulsification index in a wide range of hydrophobic substrates, and maintenance of surface activity under extreme conditions of temperatures, pH and ionic strength.<sup>2-3</sup>

Biosurfactants can be produced using industrial wastes and by-products as culture medium. In the production of surfactin from *B. subtilis*, the use of cassava wastewater is well-known; this waste seems to be an ideal match, since it is available in large amounts throughout the year and in all regions of Brazil and any country producer of cassava.<sup>1</sup>

However there is a lack of knowledge about technical feasibility of the downstream process, which uses industrial wastes as culture medium, that is, the production of biosurfactant using wastes is widely known, but the purification of the products obtained from those production are rarely reported. Downstream, is also the most important economical factor, since it represents about  $\approx 60\%$  of the total production cost.<sup>4-5</sup>

Conventional methods for purification of surfactin produced by *B. subtilis* include acid precipitation followed by extraction with organic solvents and/or adsorption.<sup>4-5</sup>

In the past ten years the ultrafiltration (UF) based downstream processing and, specifically, the two-step UF<sup>4,6-11</sup> has shown to be the most promising both in terms of the yields and purity and its scalability and it is currently being applied in the manufacturing of lipopeptides. In the first step of UF, surfactin micelles are recovered as retentate. Then, methanol or ethanol is added to the retentate in order to disrupt the micelles, and a second step of UF is carried out, however in this case, the surfactin is in solution as monomers and it is recovered in the permeate, whereas proteins remain in the retentate as they form aggregates ( $>100$  nm) in the presence of ethanol/methanol (refer to Isa et al 2007 ). Table 1 compiles the parameters and yields of surfactin UF.

**Table 1**

In most cases, the fermentation process is carried out using a synthetic culture medium. However, there have been no reports about the UF of surfactin produced using cassava wastewater as a culture medium. Cassava wastewater is a remarkable culture medium for many biotechnological processes, since cassava wastewater is composed by wide range of both macro and micronutrients (dextrose, fructose, saccharose, magnesium  $[Mg^{+2}]$ , calcium  $[Ca^{+2}]$ , manganese  $[Mn^{+2}]$ , iron  $[Fe^{+2}]$ , zinc  $[Zn^{2+}]$  and nitrogen compounds.<sup>1</sup>

Thus, we speculate that the production of surfactin using cassava wastewater as culture medium combined with the UF process in two steps would lead to a significant reduction in the cost of production of surfactin. On the other hand, using a complex medium as opposed to a well defined synthetic medium in fermentation may have an impact on the downstream processing. Therefore, the aim of this work was to evaluate the impact of using a complex medium such as cassava wastewater for the production of surfactin on its purification by the two-step UF process (Figure 1). To the best of our knowledge, this is the first study where surfactin is produced using cassava wastewater, collected by foam overflow and further purified by UF (two-steps method). In addition, the dissolved oxygen (DO) and viable cell count in the foam were analyzed, which gave an indication of the progress of the fermentative process.

## Figure 1

## MATERIAL AND METHODS

### Chemicals

The chemicals used included: acetonitrile (Sigma-Aldrich  $\geq 99.8\%$ ), bicinechonic acid kit (Sigma-Aldrich), ethanol (Sigma-Aldrich  $\geq 99.5\%$ ), bovine serum albumin (Sigma-Aldrich  $\geq 98\%$ ), deuterated dimethyl sulfoxide (Cambridge Isotope Laboratories Inc.  $>99.9\%$ ), trifluoroacetic acid (Sigma-Aldrich  $\geq 99\%$ ), and surfactin (Sigma-Aldrich  $\geq 98\%$ ).

### Surfactin production - bioprocess

#### Culture medium

Cassava wastewater is a residue from cassava flour industry, which is obtained after pressing the triturated cassava. In this work, cassava wastewater (variety of cassava IAC-

13), was collected from a flour industry and transported to the laboratory at room temperature. Next, it was boiled (3 min at 100 °C), centrifuged ( $10^4$  g during 10 min at 5 °C (Beckman Coulter, Alegra X-22r), and the supernatant was stored (-18 °C).

#### Microorganism and *inoculum*

*B. subtilis* LB5a was used as a surfactin producer. The *inoculum* was standardized according to Barros et al. (2008).<sup>1</sup>

#### Fermentation parameters and sampling

Cassava wastewater (3.0 liters working volume) was placed in a bioreactor (Bioflo® & Celligen® 310 - New Brunswick Scientific). The culture medium was sterilized at 121 °C for 20 min. Fermentation parameters used included: 100 rpm and aeration rate of 0.4 vvm (1 vessel volume per minute) maintained in the first 24 h, and then 150 rpm and 0.8 vvm from 24 to 72 h. The sensor (Mettler Toledo - INPRO 6830/12/320) of DO was programmed to measure every 30 seconds during the entire fermentation processes; the DO probe was calibrated according to the manual of BioFlo 310. Samples of the culture medium and foam were collected on a 12 h basis to analyze viable cell count, content of glucose, volume of foam and surface tension (ST). In order to obtain enough surfactin for the purification experiments, seven fermentations were carried out.

#### Volumetric oxygen transfer coefficient

Volumetric oxygen transfer coefficient (*K<sub>la</sub>*) was measured by dynamic methods. Measurements of DO were carried out using a probe (INPRO 6830/12/320). The medium (3 liters of cassava wastewater) was bubbled with nitrogen to remove oxygen. Then, aeration was started ( $2 \text{ L} \cdot \text{min}^{-1}$ ) and DO values were used to calculate the *K<sub>la</sub>*.<sup>12</sup>

## Biosurfactant recovery

The foam was collected from the top of the bioreactor during its production, as described by Barros et al. (2008). <sup>1</sup> The foam was collapsed and its volume was measured, and then centrifuged at  $10^4$  g for 20 min. Afterwards, the ST was measured in the supernatant phase using a tensiometer (Krüss GmbH K-12) by plate method. <sup>1</sup>

## Pre-purification (ultrafiltration) – crude and semi-purified biosurfactant

The collapsed foam was acidified with HCl solution (2 and 0.1 N) to pH = 2, and solution stand for 24 h at room temperature; then it was centrifuged at  $10^4$  g for 20 min. The precipitate was collected, neutralized with NaOH solution (2 and 0.1 N) and dried at 50 °C; the powder was named crude biosurfactant.

The crude biosurfactant (obtained from the seventh fermentation) was dissolved in chloroform: methanol 65:15 (v.v<sup>-1</sup>) and filtered 0.22 µm. The filtrate was recovered and dried at room temperature. <sup>1</sup> The resulting powder was classified as semi-purified biosurfactant. Yields were calculated by dividing total mass obtained of crude or semi-purified biosurfactant by the volume of culture medium (3 L). Yields were also calculated dividing total mass obtained of crude or semi-purified biosurfactant by the volume of collapsed foam (foam overflow).

## Analytical procedures – Production stage

### Measurement of surface activity

Critical micelle dilutions (CMDs) are the ST values of the sample diluted at 10-times (CMD-1) and 100-times (CMD-2). The ST measurements (CMDs) were carried out on



the centrifuged culture medium and foam samples (12 h basis) by using the plate method at room temperature in a Krüss GmbH K-12 tensiometer (K-12 model, Krüss GmbH).<sup>1</sup>

## **Purification of surfactin by two-step ultrafiltration process**

### **Process overview**

First, the purity of surfactin in crude and semi-purified biosurfactant (see surfactin concentration analysis) was measured. Then, an aqueous solution (Tris-buffer pH 8.5 - optimum solubilization of surfactin)<sup>4,5,9</sup> was made at 100 mg.L<sup>-1</sup> of pure surfactin, filtered (0.45 µm) and used as a feed in the first UF step (UF-1).<sup>6</sup> UF-1 retained the surfactin micelles and proteins (retentate), while salt and small molecules were recovered as permeate. From the retentate of UF-1, a solvent solution was prepared (ethanol 75%), followed by the second UF step (UF-2). Since ethanol solution disrupts surfactin micelles to monomers, this process aimed to retain proteins, so the surfactin can be recovered as permeate (Figure 1). After these two UF steps, high recovery and purity are expected as shows the Table 1. Basically, three analyses were carried out in all samples feed, permeate and retentate UF-1, and permeate and retentate UF-2 to evaluate the UF processes including: nanoparticle size (Dynamic Light Scattering - DLS), concentration of surfactin (High Performance Liquid Chromatography - HPLC) and protein (Bicinchininic Acid Method - BCA).

The two-step ultrafiltration process was applied following three different strategies i, ii and iii (Figure 1). In all strategies polyethersulfone (PES) membranes were used. The first strategy (i) used the crude biosurfactant solution (feed) and membranes of 100 kDa in both UF-1 and UF-2, whereas the second strategy (ii) used a crude biosurfactant solution (feed), 100 kDa in the UF-1 and 50 kDa in the UF-2. The third strategy (iii) used the semi-purified biosurfactant solution (feed), 100 kDa in the UF-1 and 50 kDa in the UF-2. Therefore, the comparasion between strategies i and ii allowed to evaluate the effect of

membrane size in the UF-2, whereas the comparasion between the strategies ii and iii the effet of initial solution of biosurfactant, crude or semi-purified.

#### Centrifugal device of ultrafiltration in two steps

The procedures were completed using Vivaspin 20 with PES – 50 and 100 kDa, containing membrane of 6 cm<sup>2</sup> of active area. For UF-1, biosurfactant solution (crude or semi-purified) at 100 mg.L<sup>-1</sup> of pure surfactin (see surfactin concentration analysis) was used as feed, in which 20-15 mL was added to the filter unit (100 kDa), centrifuged at 2205 g (10 or 20 min) and 20 °C. Next, the retentate (from UF-1 ≈0.7 mL) was dissolved in 20-15 mL of ethanol (75%) and centrifuged once again (10 or 20 min). The retentate (UF-2) was dissolved in 15-20 mL of tris-buffer (8.5). Finally, all solutions (retentate and permeate of UF-1, -2) were analyzed for surfactin concentration-HPLC, DLS and BCA.

The rejection of surfactin or protein by a membrane was defined as the rejection coefficient (R) shown below: <sup>6</sup>

$$Equation(1) R = (C_f - C_p / C_f)$$

Where C<sub>F</sub> and C<sub>P</sub> are the concentration of surfactin (C<sub>s</sub>) or protein (C<sub>p</sub>) in the feed and permeate, respectively.

It was also calculated the purity in terms of protein as mass fraction of surfactin in relation to sum of mass of surfactin and protein (P<sub>p</sub>) in the UF-1 and UF-2 as shown below: <sup>6</sup>

$$Equation(2) Pp = ((C_s / C_s + C_p)) * 100$$

The equation 2 was applied to calculate the purity in the feed, retentate and permeate.

Finally, it was calculated the total recovery of surfactin (TRS) by the equation 3, in which  $M_s$  is the mass of surfactin.

$$Equation(3) TRS = (M_{si} / M_{sii}) * 100$$

For the UF-1 ( $TRS_i$ ),  $M_{si}$  is the mass of surfactin in the retentate whereas  $M_{sii}$  is the mass of surfactin in the feed. For the UF-2 ( $TRS_{ii}$ ),  $M_{si}$  is the mass of surfactin in the permeate whereas  $M_{sii}$  is the mass of surfactin in the feed. It was also calculated the  $TRS_t$  in the UF-1 and UF-2, which  $M_{si}$  is the mass of surfactin in the initial feed (UF-1) and  $M_{sii}$  is the mass of surfactin in the permeate (UF-2). The  $M_s$  was obtained multiplying  $C_s$  by the volume of solution.

#### Analytical procedures - purification

##### Protein concentration

The total amount of protein present at each stage of the purification procedure was determined by the BCA. A calibration curve was produced, using bovine serum albumin as the protein standard solution. <sup>9</sup>

##### Surfactin concentration analysis

Surfactin concentration was determined by reverse phase HPLC from a filtered (0.45  $\mu$ m) solution (tris buffer pH 8.5 – 10 mM) of crude biosurfactant ( $\approx 1200$  mg.L<sup>-1</sup>). The system used was a Gilson 306 (Rockford, IL, USA) with a C-18 column of dimensions 250 mm  $\times$  4.6 mm, and a particle size of 5  $\mu$ m. The flow rate of the mobile phase was 1.1 mL.min<sup>-1</sup> with the initial gradient starting from 50 to 80% acetonitrile in 0.1% trifluoroacetic acid in the first 15 min. The gradient remained at 80% for 20 min before increasing to 100% for 5

min as a washing step, returning to 50% once again. A 50  $\mu$ L sample was injected into each run, which lasted 60 min, and eluent absorbance monitored at 214 nm. The system was calibrated using pure surfactin ( $\geq 98\%$ ) obtained from Sigma-Aldrich. The area of the peaks (samples) eluting at 23.18 and 27 min were identified as having the same retention times as those peaks eluting from the standard, which were added to give the total surfactin peak area.<sup>9</sup>

#### Particle size measurements - micelles

The nanoparticle sizes were evaluated by DLS, using a Zetasizer Nano ZS system (Malvern, UK).<sup>9</sup> All samples (feed; permeate UF-1; UF-2 and retentate UF-1; UF-2) were analyzed at least two times, and information about the size distribution by volume was used as a parameter.

#### Chemical structure identification of produced surfactin (strategy iii)

Three different approaches, Infrared Spectroscopy (IR), Matrix Assisted Laser Ionization Time-of-flight (MALDI-TOFMS) and Nuclear Magnetic Resonance (NMR), were used in order to investigate the chemical structure identification of produced surfactin (strategy iii). The sample was prepared for infrared analysis (FTLA2000) by mixing approximately 1 mg of produced surfactin (strategy iii) with 100 mg of KBr and pressing the mixture into the form of a pellet at 134 MPa for 2–3 min to obtain transparent pellets. The IR spectrum of the pellet was collected from 400 to 4000 wavenumber ( $\text{cm}^{-1}$ ).<sup>13</sup> MALDI-TOFMS spectra were performed using an UltrafleXtreme MALDI-TOF mass spectrometer (Bruker) operating in the reflection mode at an accelerating voltage of 22.5 kV. Mass spectra were acquired in m/z range of 700–3500 with ions generated from Smartbeam<sup>TM</sup> laser irradiation using a frequency of 2000 Hz, a lens 7 kV and the delay time was 110 ns. Matrix-suppression was set to 500 Da. External calibration was performed by using the peptide calibration

standard (Bruker Daltonics).  $^{14}\text{N}$ MR experiments were performed at 298 K using an Agilent DD2 500 MHz spectrometer equipped with a 5 mm triple resonance probe. After lyophilization, 8 mg of the produced surfactin (strategy iii) was dissolved in 600  $\mu\text{L}$  of deuterated dimethyl sulfoxide ( $^2\text{H}_6\text{-DMSO}$  CIL-Cambridge Isotope Laboratories Inc.). Resonance peaks were assigned using standard methods including correlation spectroscopy (COSY), total correlation spectroscopy (TOCSY) and nuclear Overhauser enhancement spectroscopy (NOESY). The TOCSY spectra were acquired using a mixing time of 100 ms. NOESY spectra were recorded with a mixing time of 250 and 350 ms. All two-dimensional experiments were acquired using a spectral width of 6983 Hz, a matrix size of 4096 X 512 points and relaxation delay of 1.5 s.

Data were processed using the NMRPipe/NMRVIEW software.<sup>15-16</sup> Prior to Fourier transform, the time domain data were zero-filled in both dimensions to yield a 4K X 2K data matrix. When necessary, a fifth-order polynomial baseline correction was applied after transformation and phasing.

## RESULTS AND DISCUSSION

### Surfactin production - fermentation

#### Fermentation process and recovery of surfactin

The production of surfactin from *B. subtilis* LB5a using cassava wastewater as culture medium was already reported at the following scales, Erlenmeyerflask (250 mL) and pilot bioreactor (80 L) <sup>1</sup>. Even with the subtle changes that were implemented, such as the increase of aeration after 24 h rather than 12 h, working volume, bioreactor, etc., similar process parameters were observed with those previously reported by Barros et al. (2008). <sup>1</sup> In addition, the DO (culture medium) and viable cells in the foam were evaluated for the first time, which enable a more accurate description of the fermentation process.

Figure 2 represents the viable cell counts in the culture medium and foam during the fermentation process.

As expected a similar profile between viable cell count in culture medium and foam was found since higher cell concentration in the medium favors carrying cells in foam. The analysis of cells in the foam enabled to establish that a significant number of cells were removed during the process, for instance, at 36 h  $\approx 4 \times 10^4$  viable cells per mL of foam; thus, from 330 mL (volume of foam produced at 36 h)  $\approx 10^6$  cells were removed from the bioreactor. This data supports a more accurate understanding of microbial growth. Nevertheless, it only relates to viable cells, and the high surfactin and low nutrient concentration (foam) will most likely lyse some cells; therefore, we speculate that the results were underestimated. Finally, high viable cell count reached  $\approx 10^8$  CFU when the stationary phase was between 24 and 48 h.

The ST of culture medium showed a decrease in the first 24 h, in other words, the biosurfactant content increased. As already expected, the recovery of surfactin increased due to the change in the aeration rate from 0.4 to 0.8 vvm (at 24 h). As a result, the ST values in the beginning and at the end of fermentation were similar, which indicated a high recovery of surfactin.

The surface activity of the foam was remarkable, from basically 12 h until the end of fermentation, the ST and its CMD-1 remained around 27 mN.m<sup>-1</sup>. Taking into account that the critical micellar concentration (CMC) of surfactin is  $\approx 10$  mg.L<sup>-1</sup> and CMD-1 values remained at 27 mN.m<sup>-1</sup>, it is easy to conclude that the surfactin concentration was at least 100 mg.L<sup>-1</sup>. In addition, CMD-2 data showed ST around the CMC  $\approx 30$  mN.m<sup>-1</sup>. A more accurate determination of the concentration was obtained by HPLC analysis which enabled the

determination of the exact purity of the biosurfactant in the foam (crude biosurfactant) (see purification of surfactin by two-step UF).

We believe that the recovery by foam overflow is a good strategy, when it is used in a particularly complex culture medium such as cassava wastewater. This technique is advantageous since it primarily separates surfactin and proteins from the culture medium into the foam. In addition, the high concentration of surfactin in the culture medium may act as an inhibitor on the microorganism itself leading to reduced growth and yields.

However the recovery of surfactin by foam overflow requires relatively high aeration rate in order to produce the foam. On the other hand, depleted oxygen conditions <sup>9</sup> and micro-aeration conditions,  $\approx 30\%$  of DO lead to better yields of surfactin production. <sup>17</sup> During the fermentation using cassava wastewater, the DO remained at 0% (Figure 3) and it was found the  $Kla$   $102.02 \text{ h}^{-1}$ . In this context, Fahim et al. (2012) <sup>12</sup> described that the optimum  $Kla$  for the production of surfactin was  $216 \text{ h}^{-1}$  ( $0.04\text{-}0.08 \text{ s}^{-1}$ ). Hence, the fermentations were operated at optimum aeration conditions, as demonstrated also by the high surfactin production (according to ST measurements and high volume of foam collected  $\approx 1000 \text{ mL} \pm 84$ ). However, productivity could potentially be optimized further by increasing DO and  $Kla$  to the optimum values reported by Fahim et al. (2012). <sup>12</sup>

Figure 3 shows the profile of DO and dextrose content during the fermentation.

### Figure 3

The DO profile indicates that microorganisms hardly sense the change of culture medium (due to inoculation) from nutrient broth to cassava wastewater, and based on DO, the lag phase took place within the first two hours. Then, it abruptly decreased to 0% and remained so for most of the time (from  $\approx 3$  to 68 h). This behavior is extremely good because

the microorganism growth happen at aerobic and anaerobic conditions (0%) and the fermentation happened mainly at oxygen depleted conditions which favors the production of surfactin.<sup>9,12,18,19</sup> Also, as mentioned above, the aeration rate was enough to generate foam and in this way facilitate the recovery of surfactin in the foam. Finally, at 68 h, the DO increased, indicating the death phase.

It was found that the highest volume of foam was reached at 36 h, which is aligned with the viable cell profile. It shows that surfactin production was growth-associated. On the other hand the pH increased from  $\approx 5.5$  to 7.5, this sort of fermentation (alkaline) is characteristic of *B. subtilis*.<sup>1</sup>

All seven bioprocesses showed a low relative standard deviation and very similarity with previously studies of *Bacillus subtilis* LB5a using cassava wastewater as substrate.<sup>1</sup> In each fermentation and its collected foam, 2.80 ( $\pm 0.6$  g) of crude biosurfactant was obtained, in other words, 0.93 g per liter of culture medium.

#### Purification of surfactin by a two-step ultrafiltration process

The HPLC analysis showed that crude biosurfactant had 36.14 ( $\pm 9.05\%$  w.w<sup>-1</sup>) pure surfactin; thereby,  $\approx 1010$  mg.L<sup>-1</sup> of surfactin was in the foam, and a total of 1.01 g of pure surfactin was produced from each batch (3 liters of culture medium) or 336.66 mg.L<sup>-1</sup>. This yield was lower than that reported by Isa et al. (2007)<sup>9</sup>, which achieved 583 mg of surfactin per liter of culture medium and recovered surfactin directed from the culture medium. It is worth noting that the optimization of the production of surfactin was not the focus of this study; also it was considered that 100% of surfactin was recovered in the foam however a small fraction of surfactin possibly remained in the culture medium and bioreactor walls.



## Strategy i

A feed solution ( $312 \text{ mg.L}^{-1}$ ) was elaborated based on the results of purity of surfactin (36.14%). This solution was analyzed by HPLC, and surfactin concentration was determined as  $105.85 \text{ mg.L}^{-1}$  (Table 2). The DLS analysis indicated that surfactin micelles had a diameter ( $d$ ) of 71.4 nm (Table 3). As in the feed, the permeate of UF-1 showed micelles of  $d=129 \text{ nm}$ . This together with the determination of surfactin concentration (Table 2,  $19.21 \text{ mg.L}^{-1}$ ) shows that part of the surfactin was not retained by the membrane but majority of the surfactin was rejected ( $R_s=0.82$ ) whereas for proteins  $R_p=0.68$ . Thus, the UF-1 separated most of the surfactin in micellar form from small molecules (e.g., peptides, acids, etc.) together with a large proportion of proteins.

Regarding the UF-2, the retentate from UF-1 (solubilized in ethanol 75%) was utilized as a feed solution; a solution mainly comprised by surfactin (monomers) and proteins.

Nanoparticles with  $d=466 \text{ nm}$  were observed in the retentate of UF-1. Since ethanol 75% efficiently disrupted surfactin micelles <sup>6</sup> the presence of these nanoparticles is explained as the aggregation of protein molecules in agreement with previous observations. <sup>6</sup>

The permeate of the UF-2 had nanoparticles of  $d=0.739 \text{ nm}$  which demonstrates the disruption of the micelles which led to the recovery of the surfactin in the permeate at a concentration of  $65.66 \text{ mg.L}^{-1}$ . However, the protein followed the same trend ( $R_p=5\%$ ) and was also recovered in the permeate which resulted in low purity  $\approx 44 \text{ g}$  of surfactin/  $100 \text{ g}$  surfactin and proteins. The total recovery of surfactin was 62% .

Isa et al. (2007) <sup>9</sup> demonstrated that surfactin micelles can be effectively recovered using ultrafiltration centrifugal devices with RC or PES membranes of MWCO 10 kDa, TRS<sub>i</sub> (90%) with a regenerated cellulose membrane of 30 KDa and TRS<sub>ii</sub> (91%) using a regenerated cellulose membrane of 10 KDa. These values are in agreement with those obtained here (Table 3). and those reported by Jauregi et al. (2013) <sup>6</sup> using PES 100 kDa.

The size of micelles, relatively, followed the same trend as reported by Jauregi et al. (2013) <sup>6</sup> in which concentrations between 50-100 mg.L<sup>-1</sup> of surfactin resulted in the largest micelles with d between 100-200 nm. Also, according to Knoblich et al. (1995) <sup>20</sup> surfactin micelles adopt cylindrical form due to parameters such as pH and presence of salts (CaCl<sub>2</sub> and NaCl). As a result, proteins, salts, etc., from the cassava wastewater and/or synthesized from *B. subtilis* may have some influence on the surfactin micelles shape.

In conclusion, the size and the rejection of surfactin by the membrane of 100 KDa produced using cassava wastewater as culture medium in the UF-1 were in agreement with previous findings that were described in the literature. <sup>10,6</sup>.

Consequently, UF-1 was an adequate process. However in UF-2, due to high MWCO (PES-100 kDa) proteins were also permeated which led to no purification. Therefore, strategy (ii) was applied where all parameters of UF-1 were maintained but the MWCO of membrane in the UF-2 was reduced to 50 kDa.

#### Strategy ii

As shown in Table 2, the feed solution for strategy (ii) (180.17 mg.L<sup>-1</sup> of crude biosurfactant) had nanoparticles (micelles) of similar size to those in the feed solution of strategy i (d=72.3 nm and 81.13 mg.L<sup>-1</sup> of surfactin). Samples of permeate and retentate (UF-1) and permeate (UF-2) showed similar sizes  $R_s$  and  $R_p$  to those described in strategy (i) (Table 3). This data indicated good reproducibility of the UF-1 process. However, in the retentate of UF-2, contrary to what was obtained in strategy (i), a high  $R_p$  of 49% and a low  $R_s$  of 1% was observed which proved to be a better strategy as it led to a better separation of surfactin (in the permeate) from the protein (in the retentate). Thus a higher purity ( $\approx$  59 g of surfactin/ 100 g surfactin and proteins) and higher  $TRS_t$  86.23% were obtained in strategy (ii)

However in the UF-2, the flow rate with this membrane was lower than with the higher MWCO membrane as expected and the ultrafiltration took 20 min (instead of 10 min).

In an attempt to improve the separation of proteins from surfactin further a third strategy (strategy iii) was developed where prior to the UF process the crude biosurfactant was pre-purified by acid precipitation and extraction (see 'pre-purification' in methods). It was speculated that the reduction of proteins in the feed would facilitate the separation of proteins from the surfactin.

#### Strategy iii

The feed solution (188.17 mg.L<sup>-1</sup> of semi-purified biosurfactant) had 94.24 mg.L<sup>-1</sup> of surfactin at 50.08% purity (mass of surfactin in semi-purified biosurfactant/mass of semi-purified biosurfactant). Thus, the extraction step increased the purity of surfactin from 36.14% (crude biosurfactant) to 50.08% (semi-purified biosurfactant).

Concerning the UF-1, a similar surfactin rejection,  $R_s = 0.87$ , as strategies (i) and (ii) (0.82 and 0.91 respectively) however the rejection of proteins was lower,  $R_p = 0.39$ .

In UF-2 low surfactin rejection was obtained,  $R_s = 0.02$ , as in strategies (i) and (ii), indicating that ethanol 75% efficiently disrupted surfactin micelles (crude and semi-purified biosurfactant) consequently surfactin was successfully recovered in the permeate. Similar rejection of protein was obtained here,  $R_p = 0.5$  as in strategy (ii),  $R_p = 0.49$  (Table 3). However, in strategy (iii) this process took only 10 min, indicating that fouling and/or concentration polarization was reduced due to a reduction in protein content; the feed in UF-2 (which was the retentate of UF1) for strategy (ii) contained much higher concentration of protein (93.65 mg/L) than (iii) (36,31 mg/L); the first step of ultrafiltration determined the effectiveness of the protein separation in the final second step as it is at this stage where protein deposition (fouling) hinders the permeation of protein which results in more protein

being retained in strategy (ii) than in (iii) ( $R_p = 0.75$  vs  $R_p = 0.39$ ). This effect by proteins is well documented and it has been also reported for surfactin by Chen et al. (2008) <sup>8</sup> who described that the flux declined during cross-flow UF with PES 100 membranes and it was predominantly caused by the concentration polarization, as well as weak adsorption of small amino acids and the formation of a gel layer on the membrane surface. In summary the reduction of the protein in the feed led to an improved separation of the protein from surfactin leading to a final surfactin product with increased purity ( $\approx 80$  g of surfactin/ 100 g surfactin and proteins).

**Table 2**

Comparison and evaluation of strategies i, ii and iii

Similar rejection (separation) of surfactin was obtained following the three strategies however the main difference was in the separation of protein in the second step, ie: in the purity. The worst separation of proteins from surfactin was obtained by strategy (i) as both surfactin and protein were rejected similarly in the UF-2 leading to low purity (44% purity and little improvement from that in the feed, 35%). The best results of purification were obtained with the strategy (iii)  $P_{pii}$  80% (from 53% in the feed). The strategy (ii) showed also relative good results  $P_{pi}$  59% (from 41% in the feed). Jauregi et al. (2013) <sup>6</sup> described the ultrafiltration of surfactin using a PES 100 kDa in both steps after the production using synthetic culture medium, in which the  $P_{pi}$  was higher than 92% and  $P_{pii}$  94% and Isa et al. (2008) <sup>10</sup> obtained  $P_{pi}$  88% and  $P_{pii}$  96% using a PES 10 kDa. Better results were obtained with the synthetic culture medium than with the cassava water which may be due to lower protein content in the culture (feed) of the former (75 mg/L) which facilitates the purification. Regarding the yield of the entire process (UF-1 and UF-2), high  $TRS_t$  was observed for the three strategies, i (62%), ii (86%) and iii (78).

**Table 3**

The proteins from cassava wastewater and *B. subtilis* LB5a are capable to form foam or be incorporated into the biosurfactant foam, and consequently will be recovered in the foam overflow (see item 2.2.5. - biosurfactant recovery). The production of surfactin using cassava wastewater (or any other waste) followed by the UF, perhaps is a feasible process only when associated with recovery of surfactin by the foam overflow (as a pre-purification process, previous to UF), that is, in general waste waters will have so many impurities that will make it very hard to apply UF directly, membrane fouling being one of the main problems. However foam overflow will facilitate the UF by separating first in the foam overflow the foam-forming compounds, such as surfactin and some proteins.

It is worth noting that only with the strategy (iii), where acid precipitation followed by solvent extraction (semi-purified biosurfactant) were applied prior to UF, both, high surfactin recovery ( $TRS_t$  78.25%), and effective separation from proteins were achieved and at high flux (Table 2 and Table 3). The strategy (iii) is a remarkable process since it removed majority of the proteins (concentration of proteins in the feed at 83 mg/L reduced to 18 mg/L in the permeate) and 78% of surfactin was recovered. However, the strategy (iii) added an extra purification step (solvent extraction), which would increase the cost of production.

Thus, cassava wastewater is a low-cost culture medium comprised of carbohydrates, minerals and proteins. On the other hand, considering the two-step UF of surfactin, the proteins from cassava wastewater make the purification harder, requiring solvent extraction (crude biosurfactant → semi-purified biosurfactant). The removal of proteins (e.g. precipitation) in the cassava wastewater - as previous treatment (before

fermentation) – may be considered a feasible option to improve the process without having to add so many pre-purification steps. However, the protein is a valuable nitrogen source which has a significant effect on the production of surfactin from *B. subtilis* (preferably organic nitrogen); the lower the nitrogen source - the lower the surfactin production.<sup>21</sup>

Results above bring about some interesting issues concerning production of surfactin using cassava wastewater and other biotechnological processes, which use industrial waste as culture medium. Since, on one hand the use of industrial waste as culture medium could reduce the cost of production, but on the other hand this makes the separation and purification of the products more complicated as a larger number of steps will need to be applied. Thus, this will need to be taken into consideration in the costing of the process.

### **Chemical structure identification of produced surfactin (strategy iii)**

*Bacillus* produces lipopeptides, which are classified in three families: surfactin, iturin and fengycin. Each family has a specific number of aminoacids, but with different residues at specific position. It also has different length and isomery of  $\beta$ -hydroxyl fatty acid, that is, lipopeptides have a remarkable heterogeneity of molecular weight. The analysis of MALDI-TOFMS data showed the presence of compounds within/near the range of surfactin homologous (1045-1080 m/z): (i) 1043.53; (ii) 1049.57; (iv) 1065.57; (v) 1066.58; (vi) 1068.58; (vii) 1079.60; (viii) 1082.57; (ix) 1093.55; (x) 1096.62 and (xi) 1109.60 (m/z). These molecules were clearly separated in three groups ( $\approx$  1066, 1079 and 1093 m/z). These groups probably are related to length of  $\beta$ -fatty acids.<sup>14</sup> Thus, potentially, at least 11 surfactin homologous were produced by *B.subtilis* LB5a using cassava wastewater as culture medium.

The IR analysis of produced surfactin (strategy iii) was similar to reported by Faria et al. (2011)<sup>13</sup>, that is, strongly absorbing band at 1639 cm<sup>-1</sup>, which correspond to peptide.

The NMR analysis identified three sequences of amino acids. One of them was not considered due to the very low signal intensity. Thus, 14 strong NH-signals correlations were detected between 7.207 and 9.681 ppm, in which they correspond to the two sequences of amino acids, defined in this study as S and S'- Glu1-Leu2-Leu3-Val4-Asp5-Leu6-Leu7 and Glu1'-Leu2'-Leu3'-Val4'-Asp5'-Leu6'-Val7' (Figure 4, Figure 5 and Table 4). All protons from leucine residues (4 in S and 3 in S') were identified by  $\beta\text{CH}_2$  ( $\omega I \approx 1.66$  to 1.33 ppm),  $\gamma\text{CH}$  ( $\omega I \approx 1.47$  to 1.33 ppm) and  $\delta\text{CH}_3$  ( $\omega I \approx 0.8$  ppm). Aspartic acids (S and S') were identified by two  $\beta\text{CH}_2$  crosspeaks (S - 2.62 and 2.17 ppm; S' - 2.66 and 2.11). Glutamic acid (S and S') was identified by a single pattern with two  $\beta\text{CH}_2$  signals ( $\omega I \approx 1.95$  to 1.75 ppm) and two for  $\gamma\text{CH}_2$  ( $\omega I \approx 2.04$  to 1.98 ppm). All valines residues showed common pattern with a single  $\beta\text{CH}$  ( $\omega I \approx 2.0$  ppm) and  $\gamma\text{CH}_3$  ( $\omega I \approx 0.8$  ppm) which sometimes were superposed to the  $\delta\text{CH}_3$  of the leucines. The identification of proton resonances of C3H C2H C2H' C4H  $(\text{CH}_2)_n \text{CH}_3$ , were found to be similar in S and S'; and indicated (overlapping signals) that length of  $\beta$ -fatty acid ( from 13 to 15 – expected), which is bonded to the amino acids. It also confirmed the presence of glutamic acid.

**Table 4**

**Figure 4**

**Figure 5**

It was already reported that the 3<sup>rd</sup> and 6<sup>th</sup> amino acids show D stereo configuration. <sup>22-23</sup> On natural abundance basis, L stereo configuration is significantly higher

than D stereo one. The D stereo configuration of surfactin is one of key surfactin properties such as antimicrobial.

Comparing the sequences of amino acids, previously reported, there is a trend that only the 2<sup>nd</sup>, 4<sup>th</sup> and 7<sup>th</sup> amino acids are changeable, while the 1<sup>st</sup> (Glu), 3<sup>rd</sup> (Leu), 5<sup>th</sup> (Asp) and 6<sup>th</sup> (Leu) are unchangeable. For instance, Grangemard et al. (1997)<sup>22</sup> Ile2, Ile4, Ile7 and Leu2, Val4, Leu7, Korenblum et al (2012)<sup>24</sup> Leu2, Val4, Leu7 and also the two obtained sequences S - Leu2-Val4-Leu7 and S' - Leu2'-Val4'-Val7'.

Cassava wastewater was already explored in many biotechnological processes, for instance biotransformation.<sup>25</sup> In this study we evaluated the biosurfactant production, which based on MALDI-TOFMS and NMR analysis indicated that there are at least 11 surfactin homologous, with two main amino acid sequences, resulting in a remarkable heterogeneity of molecular structure, which will potentially have different properties (surface activity, antimicrobial, etc.).

## CONCLUSION

For the first time, the UF process was applied to the production of surfactin using cassava wastewater. Solutions of crude and semi-purified biosurfactant at 100 mg L<sup>-1</sup> of surfactin result in larger surfactin micelles, which can be retained in UF-1. In UF-2, the 100 kDa membrane led to poor purification whereas high purity was achieved with the 50 kDa membrane. Therefore the best results were obtained with strategies (ii) and (iii) however the highest purity in terms of protein was obtained with strategy (iii). These results and also the comparison with our previous results obtained in the production of surfactin in synthetic medium show that the higher the protein content in the culture (feed) the more complicated the purification and therefore a larger number of steps will need to be added if a high purity product is required. Furthermore the RMN and MALDI-TOFMS analyses identified 11



potential surfactin homologous, which are composed by different  $\beta$ -fatty acids and two amino acid sequences – S and S'.

#### Acknowledgments

The authors are grateful to the São Paulo State Research Foundation (Fapesp) for their financial support, Brazilian Bioscience National Laboratory (institution of CNPEM) for RMN analysis and Polytechnic School of University of São Paulo for MALDI-TOFMS analysis.

#### REFERENCES

1. Barros FFC, Ponesi AN and Pastore GM, Production of biosurfactant by *Bacillus subtilis* LB5a on a pilot scale using cassava wastewater as substrate. *J Ind Microbiol Biotechnol* **35**:1071-1078 (2008). DOI: 10.1007/s10295-008-0385-y
2. Makkar RS, Cameotra SS and Banat IM, Advances in utilization of renewable substrates for biosurfactant production. *AMB Express* **1**:1-19 (2011). DOI: 10.1186/2191-0855-1-5
3. Pacwa-Płociniczak M, Płaza GA, Piotrowska-Seget Z and Cameotra SS, Environmental applications of biosurfactants: Recent Advances. *Int J Mol Sci* **12**:633-654. (2011). DOI: 10.3390/ijms12010633
4. Chen HL, Chen YS and Juang, RS, Recovery of surfactin from fermentation broths by a hybrid salting-out and membrane filtration process. *Sep Purif Technol* **59**:244-252. (2008). DOI: 10.1016/j.seppur.2007.06.010

5. Saharan BS, Sahu RK and Sharma D, A review on biosurfactants: fermentation, current developments and perspectives. *Genet Eng Biotechnol J* **2011**:1-14. (2012).
6. Jauregi P, Coutte F, Catiau L, Lecouturier D and Jacques P, Micelle size characterization of lipopeptides produced by *B. subtilis* and their recovery by the two-step ultrafiltration process *Sep Purif Technol* **104**:175-182. (2013). DOI:10.1016/j.seppur.2012.11.017
7. Chen HL, Chen YS and Juang, RS, Separation of surfactin from fermentation broths by acid precipitation and two-stage dead-end ultrafiltration processes. *J Membr Sci* **299**:114-121. (2007). DOI: 10.1016/j.memsci.2007.04.031
8. Chen HL, Chen YS and Juang RS, Flux decline and membrane cleaning in cross-flow ultrafiltration of treated fermentation broths for surfactin recovery. *Sep Purif Technol* **62**:47-55. (2008). DOI:10.1016/j.seppur.2007.12.015
9. Isa MHM, Coraglia DE, Frazier RA and Jauregi P, Recovery and purification of surfactin from fermentation broth by a two step ultrafiltration process. *J Membr Sci* **296**:51-57. (2007). DOI:10.1016/j.memsci.2007.03.023
10. Isa MHM, Frazier RA and Jauregi P. A further study of the recovery and purification of surfactin from fermentation broth by membrane filtration. *Sep Purif Technol* **64**:176-182. (2008). DOI:10.1016/j.seppur.2008.09.008

11. Lin S-C and Jiang H-J, Recovery and purification of the lipopeptide biosurfactant of *Bacillus subtilis* by ultrafiltration. *Biotechnol Tech* **11**:413-416. (1997). DOI: 10.1023/A:1018468723132
12. Fahim S, Dimitrov K, Gancel F, Vauchel P, Jacques P and Nikov I, Impact of energy supply and oxygen transfer on selective lipopeptide production by *Bacillus subtilis* BBG21. *Bioresour Technol* **126**:1-6. (2012). DOI: 10.1016/j.biortech.2012.09.019
13. Faria AF, Teodoro-Martinez DS, Barbosa GNO, Vaz BG, Silva IS, Garcia JS, Tótola MR, Eberlin MN, Grossman M, Alves OL and Durrant LR, Production and structural characterization of surfactin (C14 /Leu7) produced by *Bacillus subtilis* isolate LSFM-05 grown on raw glycerol from the biodiesel industry. *Process Biochem* **46**:1951-1957. (2011). DOI: 10.1016/j.procbio.2011.07.001
14. Ayed HB, Hmidet N, Béchet M, Chollet M, Chataigné G, Leclère V and Jacques P, Identification and biochemical characteristics of lipopeptides from *Bacillus mojavensis* A21. *Process Biochem* **49**:1699-1707. (2014). DOI: 10.1016/j.procbio.2014.07.001
15. Delaglio F, Grzesiek S, Vuister GW, Zhu G, Pfeifer J and Bax A, NMRPipe: a multidimensional spectral processing system based on UNIX pipes. *J Biomol NMR* **6**:277–293. (1995). DOI: 10.1007/BF00197809
16. Johnson BA and Blevins RA, NMR View: A computer program for the visualization and analysis of NMR data. *J Biomol NMR* **4**:603–614. (1994). DOI: 10.1007/BF00404272.

17. Ghribi D and Ellouze-Chaabouni S, Enhancement of *Bacillus subtilis* lipopeptide biosurfactants production through optimization of medium composition and adequate control of aeration. *Biotechnol Res Int* **2011**:1-6. (2011). DOI: 10.4061/2011/653654
18. Zimmermann HF, Anderlei T, Buchs J and Binder M, Oxygen limitation is a pitfall during screening for industrial strains. *Appl Microbiol Biotechnol* **72**:1157-1160. (2006).
19. Abdel-Wawgoud AM, Aboulwafa MM and Hassouna NAH, Characterization of surfactin produced by *Bacillus subtilis* isolate BS5. *Appl Biochem Biotechnol* **150**:289-303. (2008). DOI: 10.1007/s12010-008-8153-z
20. Knoblich A, Matsumoto M, Ishiguro R, Murata K, Fujiyoshi Y, Ishigami Y and Osman M, Electron cryo-microscopic studies on micellar shape and size of surfactin, an anionic lipopeptide. *Colloid Surfaces B* **5**:43-48. (1995). DOI:10.1016/0927-7765(95)01207-Y
21. Davis DA, Lynch HC and Varley J, The production of surfactin in batch culture by *Bacillus subtilis* ATCC 21332 is strongly influenced by the conditions of nitrogen metabolism. *Enzyme Microb Tech* **25**:322-329. (1999). DOI:10.1016/S0141-0229(99)00048-4
22. Grangemard I, Peypoux F, Wallach J, Das BC, Labbe H, Caille A, Genest M, Marger-Dana R, Ptak M and Bonmatin J-M, Lipopeptides with improved properties: Structure by NMR, purification by HPLC and structure-activity relationship of new isoleucyl-rich surfactin. *J Pept Sci* **2**:1-10. (1997). DOI: 10.1002/(SICI)1099-1387(199703)3:2<145::AID-PSC96>3.0.CO;2-Y



Micelle-destabilizing conditions	$^{\dagger}C_o$ (mg.L <sup>-1</sup> )	Membrane	TMP (psi)	Recovery (%)	Purity (%)	Flux (L(h.m <sup>2</sup> ) <sup>-1</sup> )	References
ethanol (33%) and ammonium sulfate	2,054	PES (100)	12.5	81	78	5	4
methanol (33%)	2,054	PES (100)	12.5	87	85	*NM	7
ethanol (50%)	2,550	CE (100)	8.7	80	74	220	8
methanol (50%)	571	RC (10)	29	96	93	30	9
methanol (50%)	560	PES (10)	36.5	94	96	118	10
methanol (50%)	5,000	RC (30)	30.45	95	98	*NM	11

\* Not mentioned

$^{\dagger}C_o$  = initial concentration

Table 2. Concentration of protein (PC) and surfactin (SC) in the feed, retantate (R) and permeate (P) of the first and second ultrafiltration steps (UF1 and UF2) for strategies i, ii and iii.

Ultrafiltration – First Step (UF-1)									
	PES - 100 kDa Strategy (i)			PES - 100 kDa Strategy (ii)			PES - 100 kDa Strategy (iii)		
	Feed	R	P	Feed	R	P	Feed	R	P
SC	105.	70.12	19.21	81.13	70.73	7.02	94.24	75.54	12.35
PC	194.	87.41	62.85	112.7	93.65	28.66	83.14	36.31	50.64
P <sub>pi</sub>	35	44	23	41	43	19	53	67	19
Ultrafiltration – Second Step (UF-2)									
	PES - 100 kDa			PES - 50 kDa			PES - 50 kDa		

	Strategy (i)			Strategy (ii)			Strategy (iii)		
	Feed	R	P	Feed	R	P	Feed	R	P
SC	70.1	8.57	65.66	70.73	12.94	69.96	75.54	0.94	73.74
PC	87.4	0	83.41	93.65	35.35	47.78	36.31	16.24	18.15
P <sub>p</sub>	44	100	44	43	26	59	67	5	80

SC – surfactin concentration (mg.L<sup>-1</sup>); PC – protein concentration (mg.L<sup>-1</sup>).

<sup>†</sup>P<sub>p</sub> – purity of surfactin as mass fraction of surfactin in relation to sum of mass of surfactin and protein (% w.w<sup>-1</sup>) – P<sub>pi</sub> (UF-1) and P<sub>p</sub> (UF-2).

Table 3. UF in two steps; coefficient of rejection and nanoparticle size – strategies i, ii and iii.

Ultrafiltration – First Step (UF-1)									
	PES - 100 kDa Strategy (i)			PES - 100 kDa Strategy (ii)			PES - 100 kDa Strategy (iii)		
	Feed	R	P	Feed	R	P	Feed	R	P
d	71.4	466	129	72.3	428	123	78	441	60.3
R <sub>s</sub>		0.82			0.91			0.87	
R <sub>p</sub>		0.68			0.75			0.39	
TRS <sub>i</sub>		66.78			87.18			80.16	
Ultrafiltration – Second Step (UF-2)									
	PES - 100 kDa Strategy (i)			PES - 50 kDa Strategy (ii)			PES - 50 kDa Strategy (iii)		
	Feed	R	P	Feed	R	P	Feed	R	P

D	466	60.3	0.74	428	20.9	20.9	441	35.8	22.5
R <sub>s</sub>		0.06			0.01			0.02	
R <sub>p</sub>		0.05			0.49			0.50	
TRS <sub>ii</sub>		93.64			98.91			97.62	
TRS <sub>t</sub>		62.53			86.23			78.25	

R – retentate; P – permeate

\*R<sub>s</sub> or R<sub>p</sub> - Rejection coefficient – equation 1; d – diameter of nanoparticle size (nm)

†TRS – Total recovery of surfactin – equation 3. – TRS<sub>i</sub> (UF-1), TRS<sub>ii</sub> (UF-2) and TRS<sub>t</sub> (UF-1 and UF-2).

Table 4. <sup>1</sup>H chemical shifts of two sequence of produced surfactin (strategy iii) - (<sup>2</sup>H<sub>6</sub>-DMSO at 25°C). For the non-peptide moiety, carbon atoms are numbered as in Figure 5.

	HN	αH	βH	γH	γCH <sub>3</sub>	δCH <sub>3</sub>
Glu1	9.491	4.271	1.956 1.818	2.044 1.985		
Leu2	9.567	4.218	1.500 1.472	1.472		0.828 0.787
Leu3	7.457	4.351	1.441 1.337	1.337		0.865 0.798
Val4	8.439	4.057	2.155		0.891 0.829	
Asp5	8.305	4.287	2.622 2.172			
Leu6	7.291	4.177	1.556 1.474	1.474		0.860 0.816



	Leu7	8.421	4.339	1.663	1.521	1.429	0.821	0.804
	Glu1'	9.681	4.261	1.944	1.756	2.038	2.006	
	Leu2'	9.616	4.218	1.500	1.472	1.472	0.828	0.787
	Leu3'	7.442	4.351	1.441	1.337	1.337	0.865	0.798
$S$	Val4'	8.329	4.050	2.161			0.892	0.818
	Asp5'	8.453	4.290	2.669	2.116			
	Leu6'	7.207	4.295	1.532	1.432	1.432	0.867	0.817
	Val7'	8.275	4.039	2.021			0.845	0.808

	Lipid chain	C3H	C2H	C2H'	C4H	(CH <sub>2</sub> ) <sub>n</sub>	CH <sub>3</sub>
$S$		4.933	2.801	2.292	1.557	1.213	0.833
$S'$		4.918	2.824	2.292	1.577	1.213	0.833

1 \* S (1 - sequence of amino acids)

2 † S' (2 - sequence of amino acids)