

A Bayesian network to simulate macroinvertebrate responses to multiple stressors in lowland streams

Article

Accepted Version

Creative Commons: Attribution-Noncommercial-No Derivative Works 4.0

de Vries, J., Kraak, M. H. S., Skeffington, R. A., Wade, A. J. ORCID: https://orcid.org/0000-0002-5296-8350 and Verdonschot, P. F. M. (2021) A Bayesian network to simulate macroinvertebrate responses to multiple stressors in lowland streams. Water Research, 194. 116952. ISSN 0043-1354 doi: 10.1016/j.watres.2021.116952 Available at https://centaur.reading.ac.uk/96361/

It is advisable to refer to the publisher's version if you intend to cite from the work. See <u>Guidance on citing</u>.

To link to this article DOI: http://dx.doi.org/10.1016/j.watres.2021.116952

Publisher: Elsevier

All outputs in CentAUR are protected by Intellectual Property Rights law, including copyright law. Copyright and IPR is retained by the creators or other copyright holders. Terms and conditions for use of this material are defined in the <u>End User Agreement</u>.

www.reading.ac.uk/centaur



CentAUR

Central Archive at the University of Reading

Reading's research outputs online

A Bayesian network to simulate macroinvertebrate responses to multiple stressors in lowland streams

- Authors: Jip de Vries¹*, Michiel H.S. Kraak¹, Richard A. Skeffington², Andrew J. Wade², Piet F.M.
 Verdonschot^{1, 3}
- 4 1 Freshwater and Marine Ecology, Institute for Biodiversity and Ecosystem Dynamics, University of Amsterdam, P.O. Box 94248, 1090 GE Amsterdam, The Netherlands
- 2 Department of Geography and Environmental Science, University of Reading, Reading, UK
 3 Wageningen Environmental Research, Wageningen UR, P.O. Box 47, 6700 AA
- 8 Wageningen, the Netherlands
 - * Corresponding author, j.de.vries@uva.nl

Abstract

12 Aquatic ecosystems are affected by multiple environmental stressors across spatial and temporal scales. Yet the nature of stressor interactions and stressor-response relationships is still poorly understood. This 14 hampers the selection of appropriate restoration measures. Hence, there is a need to understand how ecosystems respond to multiple stressors and to unravel the combined effects of the individual stressors 16 on the ecological status of waterbodies. Models may be used to relate responses of ecosystems to environmental changes as well as to restoration measures and thus provide valuable tools for water 18 management. Therefore, we aimed to develop and test a Bayesian Network (BN) for simulating the responses of stream macroinvertebrates to multiple stressors. Although the predictive performance may 20 be further improved, the developed model was shown to be suitable for scenario analyses. For the selected lowland streams, an increase in macroinvertebrate-based ecological quality (EQR) was predicted 22 for scenarios where the streams were relieved from single and multiple stressors. Especially a combination of measures increasing flow velocity and enhancing the cover of coarse particulate organic matter showed 24 a significant increase in EQR compared to current conditions. The use of BNs was shown to be a promising avenue for scenario analyses in stream restoration management. BNs have the capacity for clear visual 26 communication of model dependencies and the uncertainty associated with input data and results and allow the combination of multiple types of knowledge about stressor-effect relations. Still, to make 28 predictions more robust, a deeper understanding of stressor interactions is required to parametrize model relations. Also, sufficient training data should be available for the water type of interest. Yet, the 30 application of BNs may now already help to unravel the contribution of individual stressors to the combined effect on the ecological quality of water bodies, which in turn may aid the selection of 32 appropriate restoration measures that lead to the desired improvements in macroinvertebrate-based ecological quality.

34 *Keywords: Bayesian Network, ecological water quality, macroinvertebrate, multiple stressors, stream restoration*

36

1. Introduction

- 38 The ecological status of water bodies is affected by multiple stressors acting over multiple spatial and temporal scales (Allan et al., 1997; Frissell et al., 1986; Roth et al., 1996), such as increasing water
- 40 temperature, changes in flow, reduction of morphological heterogeneity and increasing nutrient loads (Friberg, 2010; Tockner et al., 2010). Moreover, these stressors may interact, having synergistic,
- 42 antagonistic or additive effects on the ecological status of freshwater bodies (Jackson et al., 2016; Piggott et al., 2015). The combined effects of these multiple interacting stressors are, however, still poorly
- 44 understood (Folt et al., 1999; Jackson et al., 2016), since stressor-response relationships observed in controlled experiments are specific to organisms, stressors and environments and are therefore difficult
- to extrapolate to the field (Jackson et al., 2016).

The lack of understanding of the combined effects of multiple interacting stressors may also explain why
knowledge of the effect of specific management interventions on ecological water quality is still limited
(Palmer et al., 2005; Pander and Geist, 2013). Consequently, a high proportion of restoration measures
are ineffective, even now (dos Reis Oliveira et al., 2020; Palmer et al., 2010). Hence, to increase the
effectiveness of restoration measures, we first need to increase our knowledge of how ecosystems
respond to multiple stressors and to unravel the contribution of the individual stressors to their combined

effect on the ecological status of waterbodies.

54 Model simulations provide the opportunity to relate the state of an ecosystem to environmental changes as well as to restoration measures and simultaneously provide understanding of the underlying ecological

- 56 interactions. Consequently, models may be used to predict the effects of management interventions on ecosystem states in space and time and thus provide valuable tools for water management. Over the last
- 58 decades, several ecological prediction models have been developed, ranging from mechanistic representations of environmental processes to food web models and statistical data-driven models
- (Janssen et al., 2015). For the latter, techniques have been used such as decision trees, artificial neural networks, generalised linear and additive models, fuzzy logic models and Bayesian Networks (BNs)
 (Pistocchi, 2018). The construction of such statistical ecological prediction models can be data-driven, knowledge-based or a combination of both (Mouton et al., 2009; van Echelpoel, 2020). A review of the
- 64 advantages and drawbacks of selected modelling techniques indicated that BNs are promising tools for the combined application of expert knowledge and ecosystem measurements (de Vries et al., 2020a; van
- 66 Echelpoel, 2020).

BNs are causal network models in which nodes depict (environmental) factors and in which dependencies

- 68 between nodes are expressed as probabilistic relationships (McCann et al., 2006). The main advantage of this type of model is that the full range of available knowledge on cause-effect relations can be used,
- originating from experts, mechanistic modelling output, literature and experimental and observed data
 (Landuyt et al., 2013; McCann et al., 2006), integrating the scattered knowledge on cause-effect relations
- in water bodies. Moreover, in these models, samples with incomplete datasets can still provide knowledge (Barton et al., 2012). The uncertainty associated with the input data is explicitly accounted for, and the
- 74 predicted outcome is reported as likelihoods (Uusitalo, 2007). In addition, BNs provide a visualisation of the causal relationship between the predictors, which helps with communication of the model. Limitations
- of this model type are the lack of representation of feedback-loops, and the requirement for discretising continuous data (Uusitalo, 2007). However, for evaluating stressor-effect relations in water bodies we
- 78 considered that the numerous advantages of BNs outweighed these drawbacks. The aim of the present study was therefore to develop and test a Bayesian Network for simulating responses of stream

- 80 macroinvertebrates to multiple stressors. Since we anticipated that stressor-effect relationships would be context-specific, model predictions were approached using water-type and region-specific relationships
- 82 (de Vries et al., 2020b). To this end, a BN model was developed which included the links between macroinvertebrate-based ecological quality and stream characteristics for a single water type, the
- temperate, sandy lowland streams within the North-western European plain. The availability of an extensive dataset with measurements of multiple stressors and ecological responses for Dutch lowland
- streams enabled us to develop this BN-model. The developed model was then applied to predict the influence of stream restoration management scenarios on ecological quality as represented by
- 88 macroinvertebrates.

90 **2. Methods**

2.1 Study area

92 The studied lowland streams were located on the ice-pushed ridges in the Veluwe area in the centre of the Netherlands (Figure 1). The land use in the catchments consisted of agricultural fields, urban areas
94 and deciduous and coniferous woodlands. Mean annual rainfall in the study area was 850 mm and daily temperature varied between -16 and 29 °C. The flow velocities in the groundwater- and precipitation-fed
96 streams varied strongly (10-80 cm/s). The stream bottoms consisted of sand and gravel.



98 Figure 1. Study area with sampling sites in the selected streams.

2.2 Macroinvertebrate and environmental data

100 The data was collected by the Dutch Water Authority 'Vallei and Veluwe' during regular monitoring programmes over the period 1981-2017. In total, 208 sites in the upper courses of the lowland streams 102 were selected. At these sites macroinvertebrate abundance data was collected as a part of regular monitoring programs. For each macroinvertebrate sample the ecological quality ratio (EQR) was 104 calculated according to the Dutch assessment system, which expresses the ecological quality of a water body (ranging from 0-1.0) as a fraction of the reference situation (1.0) (Van der Molen et al., 2016). In 106 addition, for each macroinvertebrate sample, the mean preference score (ranging from 1-5) for several environmental variables of all species present in that sample was calculated using relative abundance 108 frequencies. To this end, an environmental preference dataset was used (Verberk et al., 2012). Environmental variables that were monitored at the same locations and at the same moment as the 110 macroinvertebrate samples included water temperature, dissolved oxygen concentration, stream velocity, shading, total phosphorous concentration, biological oxygen demand, chlorophyll concentration, 112 stream gradient, silt cover, macrophyte cover, coarse particular organic matter cover, and the presence of wood and gravel. However, not all variables were measured at all sites and on all occasions and 114 therefore only environmental monitoring data was included when macroinvertebrate abundance data and at least a single environmental variable were monitored simultaneously. This resulted in a set of 933

samples (Figure 1).

2.3 BN theory

- 118 In short, BNs consist of causal network structures in which nodes, representing important system variables, are related to each other through arrows, representing dependencies (Charniak, 1991). The
- 120 state of a node is determined by the states of its parent nodes. This approach is described by Bayes'

theorem, in which prior probabilities are updated given the likelihood of the data to generate a posterior

- 122 probability distribution (Ellison, 2004). The type of relation between a node and its parent nodes, as well as the associated uncertainty, are recorded in a conditional probability table (CPT).
- 124 CPTs can be based on multiple types of data, including expert knowledge, process-based modelling output, literature-based values, experimental and observational data. Observational data is preferred, but
- 126 when gaps are present in the dataset, other types of evidence may be used to quantify the relationships between the nodes. CPT relations that are initially based on expert knowledge can also be trained by using
- 128 field observations. Hence, BNs have the advantage of being able to deal with incomplete datasets, and of providing ways to combine different sources of knowledge (Uusitalo, 2007).
- A BN captures relations between a set of variables, which may be uncertain, probabilistic, or imprecise.When the predictions are used in decision making, the explicit reporting of the associated uncertainty and
- 132 the variability in the model results provides an advantage of this approach over deterministic methods that lack this reporting (McCann et al., 2006). Another advantage of BNs is that calculations can be made
- in the two directions of the arrows between the nodes: the values of child nodes can be calculated given the values of the parent nodes and vice versa. Consequently, BNs can be used to predict the outcome of
 scenarios given a set of causal variables, but also as diagnostic tools to deduce the probabilities of causes
- given the observed consequences, by using the dependencies in the model structure backwards (Barton
- 138 et al., 2012; McCann et al., 2006).

2.4 Model development

- 140 A five-step model development process was adopted (Marcot *et al.* 2006) following several guidelines (Aguilera et al., 2011; Chen and Pollino, 2012; Landuyt et al., 2013). 1) Model structure: An influence
- 142 diagram was set up showing the causal relations between the environmental variables and the macroinvertebrate-based EQR. 2) Model parametrisation: The CPTs picturing the relationships between

- 144 the nodes in the model structure were defined using expert knowledge, and model-based and literaturebased relationships. In this step also continuous variables were discretized. 3) Model training: The CPTs
- were trained using observations. 4) Model testing: Model performance was tested using independent observations. 5) Model application: A final model version for application was trained using all available
- 148 data.



- 150 Figure 2. Model structure of the BN relating the macroinvertebrate-based EQR to environmental variables. BOD: Biological Oxygen Demand, CPOM: Coarse particular organic matter, DO: Dissolved
- 152 oxygen concentration, FQ: Food quality.

Model structure (step 1)

- 154 The constructed BN represents a causal network of the environmental factors that influence macroinvertebrate assemblages. The chosen outcome variable was the EQR. The development of the
- early stages of the model structure was described in Skeffington et al., 2014s. Based on literature and

input from stream macroinvertebrate experts, the key environmental factors that influence the EQR in 158 this specific water type and region were selected, including temperature, oxygen concentration, flow velocity, food quality and substrate variability (Sandin and Johnson, 2004; Verberk et al., 2012; 160 Verdonschot et al., 1998). These factors score the response to the environmental variables on a scale from 0-1, thus giving the user the opportunity to see which stressor is most limiting for a high EQR. The optimal 162 values of these key factors were based on water-type and region-specific preferences of the reference macroinvertebrate assemblage (Verdonschot et al., 2000). Next, predictors of those environmental 164 variables that span local to regional spatial scales were included, resulting in the model structure depicted in Figure 2. The selection of the included variables was made to cover all relevant processes from reach-166 to catchment scale, but at the same time aimed to limit model complexity. In addition to the environmental variables, five nodes were included that represent the average preference score of the 168 observed macroinvertebrate assemblage for the variables flow velocity, CPOM, silt, gravel and wood. These scores are based on a preference database that lists species-specific preferences for environmental

- 170 variables, based on experimental and distribution data (Verberk et al., 2012), and range from 1 (low preference) to 5 (high preference). Inclusion of these nodes served as an additional source of information
- about the quality of a water body based on the preferences of the local macroinvertebrate assemblage.

Model parametrisation (step 2)

- 174 Initially, the relationships between the nodes in the model were based on literature, mechanistic modelling outcomes and expert judgement (Table A.1). When possible, a relationship was expressed as
- an equation. Discretisation was either based on equal intervals or on equal frequency to assure an even spread of data (Chen and Pollino, 2012). The number of discretisation classes for each node was either 4,
- 5 or 6, balancing a minimum resolution to picture environmental processes with sufficient data availability per class.

Training and testing of the network (step 3 and 4)

Step 3) and 4) were combined in a k-fold cross-validation context (Marcot, 2012). The dataset was split
into 3 parts, of which 2 parts were used for training the network and 1 part for testing the network
performance. For a stable validation outcome among trained model variations, subsets of data for crossvalidation can be made using stratified classes. Although this was not applied here, the subsets of data
did have a similar distribution of EQR classes. Model training and testing was done for 3 consecutive runs,
where in each run another part of the dataset was used for testing. The resulting metrics were then averaged for overall model performance. Cross-validation was performed on several model variations to
test the influence of differences in structure and parametrisation on the prediction performance, i.e.

190 macroinvertebrate preference data (Table 1). Sensitivity analysis of the network was performed to identify the factors that had the strongest influence on the target node.

discretisation method, number of discretisation classes and the inclusion/exclusion of nodes representing

- 192 It was thought more valuable to compare the model results as a continuous EQR-value to observed continuous values, as the use of EQR classes would not be informative enough in practice. Conventional
- 194 metrics such as the number of correctly classified instances only use the classified output of the model, expressed as discrete values, and are therefore less suitable for testing the performance of the model in
- 196 predicting the actual continuous EQR. Therefore, in this study, performance was tracked using the correlation between the observed and predicted EQR-scores (Marcot, 2012), although the performance
- 198 might be more strictly assessed than by using class-based metrics. The EQR scores used were expected values predicted by the target node, which is the average of the discretized classes weighted by the 200 probability of occurrence.

To develop and test the BN model, the Netica BN software was used as a modelling shell (Norsys, 1998).

202 This software provides a graphical user interface, can handle input of continuous data, provides ways to perform sensitivity analysis and can work in batch mode to more easily run the model for multiple sites.

204 Scenario analysis (step 5)

Based on the performance analysis, the best performing model variation was selected. Next, this model

- 206 was trained with all available data (Marcot, 2006) (Table A.3) and subsequently applied to predict the influence of stream restoration management scenarios on macroinvertebrate-based ecological quality. To
- 208 this end, sites were relieved from either one or multiple stressors (Table 2), in which only combinations of scenarios that targeted at least two different key factors were considered. A comparison was made
- 210 between the effect of removing single and multiple stressors per stream or stream stretch.

Table 1. Tested model settings.

Model setting	Tested settings
Number of discretisation classes	4, 5, 6
Discretisation method	Equal Interval, Equal Frequency
Trait preference nodes	Present, absent

212

Table 2. Restoration scenarios. T: Temperature, S: Shading, V: Flow velocity, TP: Total phosphorous

214	concentration,	CPOM: Coarse	particular	organic matter	, Sub: Substrate.
-----	----------------	--------------	------------	----------------	-------------------

Scenario	Stressor alleviation
Т	Decrease temperature to 10 °C
S	Increase shading to 100%
V	Increase flow velocity to 0.5 m/s
ТР	Decrease TP to 50 μg/L
CPOM	Increase CPOM cover to 70%
Sub	Add presence of wood and gravel
T+V	Adjust temperature and velocity
T+CPOM	Adjust temperature and CPOM
T+Sub	Adjust temperature, wood and gravel

S+V	Adjust shading and velocity
S+CPOM	Adjust shading and CPOM
S+Sub	Adjust shading, wood and gravel
V+TP	Adjust velocity and TP
V+CPOM	Adjust velocity and CPOM
V+Sub	Adjust velocity, wood and gravel
TP+CPOM	Adjust TP and CPOM
TP+Sub	Adjust TP, wood and gravel
CPOM+Sub	Adjust CPOM, wood and gravel
All	All of the above scenarios combined

216 **3. Results**

The first steps in developing the model were constructing the network structure and then informing it
with literature- and expert-based knowledge (step 1 and 2). In the third step, the knowledge-informed network was trained using actual monitoring data. Training the network with monitoring data resulted in
adjusted probabilities, directly affecting 17 nodes, with a maximum change in probabilities of 60%. For instance, there was a relatively high number of high-gradient streams in the dataset. Consequently, the
corresponding probabilities were adjusted such that for any new datapoint without observations for stream gradient, the model assumed a higher prior probability that it is a high gradient stream. This in
turn altered the prediction of the status of the target node, the ecological quality expressed by the EQR.

This adjustment is reflected by the larger bar in the top right node of Fig. 3b compared to Fig. 3a.



Figure 3. BN model for relating the macroinvertebrate-based EQR to environmental variables a) before and b) after training with monitoring data. Node bar plots describe the prior probabilities of states. For node colours, see Fig. 2. Node states are listed in Table A.2.

Table 4. Performance of model variations from the model evaluation as spearman rank correlation between observed and predicted EQR scores.Correlations are averaged over three pairs of training & test data sets. For all correlations

p≤0.05. Trait preference nodes indicate preference
 for environmental factors as indicated by the observed assemblage.

236	Number of classes	Trait preference nodes included	Discretisation method	
			Equal	Equal
			interval	frequency
	4	Ν	0.25	0.26
120		Υ	0.24	0.28
230	5	Ν	0.27	0.26
		Υ	0.27	0.29
	6	Ν	0.25	0.32
		Υ	0.27	0.35



Figure 4. Sensitivity analysis for the best performing model variation. For abbreviations, see Table 2.

242

240

244

246 In step 4 of the model development, the network was tested using a part of the dataset applying a 3-fold cross-validation. The performance of the tested model variations (Table 4) was expressed as correlations

between the observed and the predicted EQR scores and showed scores up to 0.35, expressing a relatively

poor predictive performance. The model variation performing best was obtained by incorporating 6

250 discretisation classes, using equal frequency discretisation, and including the trait preferences nodes.

The sensitivity analysis shows the influence of the environmental factors on macroinvertebrate-based
 EQR, the target node, in decreasing order (Fig. 4), revealing that temperature, velocity and CPOM had the strongest influence, whereas the factors macrophytes, stream gradient and total phosphorous
 concentration had a very limited influence.



- Figure 5. Comparison of mean EQR model predictions and mean EQR observations for the studied streams. Boxes are inter-quartile ranges (IQR, 25th to 75th percentile) with whiskers extending to -/+ 1.5 * IQR.
- 258 Statistical pairwise differences were calculated using Wilcoxon test, *: p <= 0.05, **: p <= 0.01, ***: p <= 0.001, ****: p <= 0.0001.</p>



Figure 6. Observed flow velocity (m/s) and average abundance-weighted flow-preference score for the macroinvertebrate assemblages present in samples from the streams Egelbeek and Zwaanspreng. Preference scores range from 1 to 5. The colours of the points indicate the observed EQR.

This best performing model variation was subsequently applied to compare the model EQR predictions

- with the observed EQR per stream (Fig. 5), showing that in half of the cases, the EQR was predicted well.This concerned mainly streams with a relatively low EQR. In contrast, in the other half of the streams,
- having a relatively high observed ecological water quality, the predicted EQR was lower than the observed
 EQR. In these underpredicted cases, either the model judged the environmental variables too severely, or
- 270 the observed EQR was overrepresenting the actual ecological quality, as a result of a too optimistic underlying assessment system. To gain more insight into these underpredictions, the two most deviating
- 272 cases, the Zwaanspreng and Egelbeek, were considered in more detail. To this end, the average preference score of the macroinvertebrate assemblage was calculated for each sample for the factor flow
- velocity, one of the most influential environmental variables (Fig. 4) and the only factor for which enough preference data was available (Fig. 6). The mean flow velocity preference scores for these samples was
 relatively high (mean preference score: 3.6 out of 5), and also the flow velocity was generally high (mean 0.31 m/s). Likewise, the observed EQR was also high (mean 0.81). This points to the model having
- 278 underpredicted the EQR of these sites, based on the factor flow velocity. However, flow velocity is only one of the factors determining the EQR and therefore, also other factors might have contributed to the
- 280 underestimated EQR. However, as there is insufficient data available for the actual assemblage preference for the other environmental factors, we could not evaluate the contribution of these factors to the 282 underpredictions of the EQR.

In the scenario analysis (step 5), the model was used to predict the effect of relieving the stream from single and multiple stressors on the target node, the EQR. For all streams combined, significant differences in EQR were observed when compared with the current conditions (Fig. 7a). Yet, for scenarios involving the relief of a single stressor, more negative than positive effects were observed. In contrast, when a

some of the streams, the effects of taking away the stressors could not be predicted (not shown), which

combination of stressors was removed, the majority of scenarios showed positive effects on the EQR. In

might be due to inconsistencies between the observed and the scenario-based variables in the model, where nodes receive contradicting input. When the scenario effects were considered per individual stream, there was a high variation in the results (Fig A1). Nevertheless, for half of the streams clear

- 292 management effects were still observed. To illustrate this, the Hierdense beek and Tongerense beek were considered in more detail, because these streams showed the clearest effects of stressor relief and had
- 294 the largest dataset, respectively. Moreover, the specificity of the predictions was increased when the samples were grouped in stream stretches that represent a specific waterbody subtype within similar
- 296 surrounding conditions, as can be seen for the upstream stretch of the stream Hierdense beek (Fig. 5). For this stretch of the Hierdense beek and for the stream Tongerense beek several positive effects of
- 298 management scenarios were observed (Fig. 7b, 7c). Relieving the stream from most single stressors and stressor combinations increased the EQR. In contrast, scenarios involving an increase in velocity showed
- 300 negative effects on the EQR, except when this measure was combined with increased CPOM cover, where a strong positive effect was seen. Especially the combined approaches that increased CPOM cover and
- 302 flow velocity or CPOM cover and substrate quality (wood and gravel presence) had a positive effect on the mean EQR of both streams.



Figure 7a. Model predictions of restoration scenarios for all streams combined (based on a total number
 of 9891 model runs, with a variable number of model runs per scenario due to inconsistencies). For
 scenario abbreviations, see Table 2. Asterisks indicate significant differences in EQR compared to the
 current conditions (CC) (Wilcoxon test).



Figure 7b. Model predictions of restoration scenarios for the Hierdense beek (upstream) (based on a total
 of 215 model runs). For scenario abbreviations, see Table 2. CC gives the model predictions for the current conditions. Asterisks indicate significant differences in EQR compared to the current conditions (Wilcoxon
 test).



- Figure 7c. Model predictions of restoration scenarios for the Tongerense beek (based on a total number of 1552 model runs). For scenario abbreviations, see Table 2. Asterisks indicate significant differences in
 EQR compared to the current conditions (CC) (Wilcoxon test).
 - 4. Discussion
- 322 The aim of our study was to develop and test a Bayesian Network for simulating macroinvertebrate-based
 - 324 model was developed for a specific water type in a single region, where multiple stressors affected the stream ecosystem quality. Although surrounded by substantial margins of uncertainty (as seen in Fig. 7),

ecological water quality based on the responses of stream macroinvertebrates to multiple stressors. The

- 326 the BN clearly showed the positive influence of restoration measures on the ecological quality of the studied lowland streams. Below we will discuss the performance of the BN in the scenario analyses, the
- 328 complexity of predicting the effects of multiple stressors on macroinvertebrate-based ecological quality and how this approach can be applied in stream restoration management.
- 330 4.1 BN model development

water type.

BNs are promising as tools in restoration management, as they offer a way to include expert knowledge
with associated uncertainties in combination with monitoring data and output from process-based modelling. In addition, the explicit expression of the associated uncertainty and the clear visualisation of
the causal model structure are advantages of this technique, which make it a suitable tool to support water managers in decision making (Barton et al., 2012; Uusitalo, 2007). However, to be able to train the
knowledge-informed network using observations, for each pair of connected nodes, there should be a set of data available that covers the full range of all possible combinations of node states (Cain, 2001). This is
a requirement which may be difficult to comply with in practice, especially when the focus is on a specific

- 340 In the development of our BN model, choices had to be made to deal with the inherent complexity of aquatic ecosystems. To this end, the main predictors of the macroinvertebrate-based EQR were selected.
- 342 However, there was a trade-off between the desired model complexity and the availability of training data, where a lack of data would decrease model performance (see also Marcot et al., 2006). Hence, to
- select the optimal model variation, multiple model structures and parameterisations were tested. In the comparison of these slightly adjusted models, equal frequency discretisation gave better predictive
 performance than discretisation based on predefined class boundaries (however, compare Boets et al., 2015). Although all discretisation methods imply a simplification of continuous data (Aguilera et al., 2011),
- 348 using equal frequency discretisation ensures that each class of a node is represented equally in the data, which supports a better training of the conditional probabilities in the network. Also, the inclusion of the
- 350 preference nodes slightly improved the predictions.

Our results showed the impact of restoration measures in the scenario analysis compared to the current

- situation, but the overall absolute performance of the BN model was still limited. Especially for streams with a high observed ecological quality, the EQR was underpredicted by the model. This might be partly due to gaps in the dataset, consequently, it was not possible to train each knowledge-based CPT with observed data (Table A.3). A possible explanation may also be that the model only predicts the effects of changes in environmental factors on macroinvertebrates, whereas in reality, dispersal and biotic interaction filters also determine the macroinvertebrate assemblage composition and therefore the ecological quality of a specific site (Poff, 1997). In addition, the interactions between environmental factors are not completely understood and cannot be fully incorporated. Moreover, the model is static and therefore assumes that the assemblage is in equilibrium with the environmental conditions at each
- these complexities, which are not well understood, could have influenced the performance of the model.

site (Austin, 2002), but this is not always the case (Belyea and Lancaster, 1999; Wiens, 1984). Together,

Therefore, the current model is not yet thought to be acceptable for application as such, given that 364 predictions are not yet in accordance with the observations. With a more complete dataset, testing of additional model variations and an increased insight in stressor interactions to improve model relations, 366 this model type might be further applied as a tool in restoration management.

4.2 Multiple-stressor effects on macroinvertebrate-based ecological quality

- 368 Waterbodies are generally subjected to multiple stressors (Birk, 2018). This creates a complex task for water managers who aim to improve the ecological status of stream ecosystems. In addition, stressor
- 370 interactions may take place that either enhance the added effects of additional stressors (synergism) or decrease these combined effects (antagonism) (Folt et al., 1999). Such interactive effects are specific to
- 372 stressors, organisms and environments and consequently are difficult to predict (Jackson et al., 2016).With this added complexity, simulating ecological quality remains a complex task, as our study showed.
- 374 Despite this complexity, the present BN scenario analyses showed that ecological quality can be improved when the streams are relieved from specific stressors or combinations thereof, whereas other restoration
- 376 scenarios may prove to be less effective. For the studied streams, the strongest positive effect resulted from increasing flow velocity in combination with the presence of CPOM, whereas only improving flow
- velocity yielded no positive effect. This may be explained by the interaction between flow velocity andCPOM: only increasing stream velocity would not safeguard the variation in flow required for patches of
- 380 coarse material to persist, providing necessary habitat for stream organisms (de Brouwer et al., 2019). To gain more insight in the interaction between flow velocity and CPOM cover, these key environmental
- factors could be included in the network in more detail than they are now. The added value of combining restoration scenarios was also observed for the scenarios that enhanced the presence of wood and gravel substrate and the cover of CPOM. In the scenarios where the streams are relieved from the individual
- stressors, already a positive impact is seen, but when the stream is relieved from both stressors

- 386 simultaneously, the macroinvertebrate-based ecological quality improves even more than expected based on the contributions of the single stressors, which could point at a positive synergistic interaction
- 388 of stressor relief. Similarly, such interactive effects on macroinvertebrates have been observed for other environmental stressors (Beermann et al., 2018; Jackson et al., 2016). Yet, for the other combined
- 390 scenarios in the present study where multiple stressors were adjusted, no interactive effects were observed. Indeed, also for other water bodies it was reported that additive effects of multiple stressors 392 prevail (Gieswein et al., 2017). However, the current model is partly knowledge-informed and not completely based on data. This is especially the case for the target node, where the relationship picturing
- the combination of multiple stressors into a combined response was based on expert knowledge.

To better quantify the interactions between the stressors of interest, additional statistical analyses could 396 be carried out on a more extensive dataset (Feld et al., 2016; Glendell et al., 2019). In addition, experiments may help to disentangle the interactive effects of multiple stressors (Elbrecht et al., 2016;

- 398 Verberk et al., 2016). Only when we have more knowledge about the nature and interactions of stressorresponse relationships for specific species and complete assemblages, can we develop modelling of
- 400 multiple stressor impacts further. In turn, the application of models can show us where these knowledge gaps persist and where additional experiments might be needed to better understand underlying
- 402 processes. Consequently, BNs and other approaches are complementary in their contribution to an increase of the understanding of multiple stressor effects.
- 404 Apart from the interaction between stressors, other studies showed that choosing measures based on identifying multiple stressors covering the entire catchment proved to be more effective (dos Reis Oliveira
- 406 et al., 2020; Feld et al., 2011; van Puijenbroek et al., 2019). This illustrates the significance of simultaneously considering multiple stressors over multiple scales for effective stream restoration.

- 408 In conclusion, the present model exercise demonstrated that applying different scenarios enhances the understanding of the effects of combinations of measures on macroinvertebrate-based ecological quality
- 410 and may aid in selecting and prioritizing the most promising restoration measures, as discussed below.

4.3 BNs as tools in restoration management

- 412 Nowadays, in the practice of stream restoration, the selected measures are still strongly based on assumptions rather than proofs of their positive effects on the ecological status of stream ecosystem (dos
- 414 Reis Oliveira et al., 2020), which was the main motivation to perform the present study. The application of the current BN model indeed enhanced the insights into the possible effects of management scenarios
- 416 on the ecological quality as represented by macroinvertebrates. Hence, these model predictions may be used to inform water managers which measures to prioritize in restoration management to effectively
- 418 alleviate stress. This increases the chance that the applied restoration measures do indeed lead to the desired improvement in the ecological status of stream ecosystems. Whereas we used the BN model to
- show the relative impact of (combinations of) restoration measures on macroinvertebrate-based ecological quality, such models can also be used 'backwards' in a diagnostic approach to find causes for
 observed symptoms (Feld et al., 2020; Trigg et al., 2000).

Ideally, a model performing well, tailored to the study area, would give insight into which environmental

- 424 factors would produce most effect. For the manager, the next step would be to identify how these variables might be targeted, by linking these to actual restoration measures. However, this prioritisation
- 426 is often not just based on the outcome of the model. In these scenario analyses, the use of site-specific knowledge would permit the manager to decide which variables to prioritize, for example, knowledge of
- 428 the possibility and cost of certain measures, and of restoration efforts and disturbances that have taken place in the past.

- 430 As shown here, scenario analyses can be especially informative in situations where multiple stressors are acting. In the case of a single dominant stressor, a specific measure may be more easily selected, but for
- 432 a situation with a more even contribution of multiple stressors, selecting and prioritizing restoration measures may not be straightforward. In these cases, scenario analyses may help to choose a combination
- 434 of measures to alleviate the pressure on the ecosystem and to improve the ecological water quality.

The current model was designed and trained for a single area and water type. When applied to other areas, the main model structure can still be used as a starting point, although the choice for key environmental factors, parametrisation of the CPTs, calibration and validation should be carried out in a way tailored to the water type and region of interest.

Ultimately, in the application of BNs, challenges remain with the abovementioned complexities. In addition, Kaikkonen et al. (2021) list the remaining challenges of BNs used in environmental management, such as models lacking validation, unclear discretisation methods, and lack of clarity about the source of

- 442 expert knowledge. Indeed, most BN applications fail to test the predictive ability of the model (Death et al., 2015). As described here, discretisation and validation of the model outcomes is not straightforward.
- 444 Better reporting of such challenges associated with these technical aspects may therefore improve future robustness of BN applications. In addition, recent technical developments might further increase the
- 446 possibilities of BN applications, such as the use of hybrid networks that can represent continuous variables without the information loss associated with discretisation (Kaikkonen et al., 2021).
- The success of applying BNs for similar purposes in the future depends on the availability of high-quality data and the possibility to include a more fundamental understanding of the complexity of ecosystems,
- 450 with context-specific knowledge on how interactions between multiple stressors affect macroinvertebrate assemblages. The current approach has contributed to an increased understanding of

452 the complexity of these aquatic ecosystems. Moreover, our study showed how BNs can be used in a scenario analysis to select and prioritize the most promising restoration measures.

454

5. Conclusions

- 456 In this study, the application of BNs for simulating the effects of multiple stressors on macroinvertebratebased ecological water quality was tested. Although the predictive performance can be further improved,
- 458 our application illustrated how these models can be used to increase our knowledge of how ecosystems respond to multiple stressors. To make predictions more robust, a deeper understanding of stressor
- 460 interactions is required. Also, sufficient training data should be available for the water type of interest. Still, BNs allow us to make steps in unravelling the contribution of the individual stressors to their
- 462 combined effect on the ecological quality of water bodies. This in turn may aid the selection of appropriate restoration measures that lead to the desired improvements in ecological water quality.

464 Acknowledgements

The early part of this research was supported by the REFRESH Project (EU Seventh Framework

- 466 Programme, Grant Agreement: 244121). In addition, this research was supported by STOWA (Dutch Foundation for Applied Water Research). We thank the water authority Vallei and Veluwe for kindly
- 468 providing us with their monitoring data.

Author contributions

- 470 RAS, AJW and PFMV developed the initial BN. JdV further developed the BN and analysed the data. JdV, PFMV and MHSK led the writing of the manuscript. All authors contributed to the review and revision of
- the model and the manuscript, and approved the final article.

474 **References**

476	Aguilera, P.A., Fernández, A., Fernández, R., Rumí, R., Salmerón, A., 2011. Bayesian networks in environmental modelling. Environ. Model. Softw. 26, 1376–1388. https://doi.org/10.1016/j.envsoft.2011.06.004
478	Austin, M.P., 2002. Spatial prediction of species distribution: An interface between ecological theory and statistical modelling. Ecol. Modell. 157, 101–118. https://doi.org/10.1016/S0304-3800(02)00205-3
480	Bartholow, J.M., 2002. Stream Segment Temperature Model (SSTemp) version 2 Software. Revised US Geological Survey computer model and documentation.
482 484	Barton, D.N., Kuikka, S., Varis, O., Uusitalo, L., Henriksen, H.J., Borsuk, M., Hera, A.D. La, Farmani, R., Johnson, S., Linnell, J.D.C., 2012. Bayesian networks in environmental and resource management. Integr. Environ. Assess. Manag. 8, 418–429. https://doi.org/10.1002/ieam.1327
	Belyea, L.R., Lancaster, J., 1999. Assembly Rules within a Contingent Ecology. OIKOS 86, 402–416.
486 488	Birk, S., 2018. Detecting and quantifying the impact of multiple stress on river ecosystems, Multiple Stressors in River Ecosystems: Status, Impacts and Prospects for the Future. Elsevier Inc. https://doi.org/10.1016/B978-0-12-811713-2.00014-5
490 492	Boets, P., Landuyt, D., Everaert, G., Broekx, S., Goethals, P.L.M., 2015. Evaluation and comparison of data-driven and knowledge-supported Bayesian Belief Networks to assess the habitat suitability for alien macroinvertebrates. Environ. Model. Softw. 74, 92–103. https://doi.org/10.1016/j.envsoft.2015.09.005
494	Cain, J., 2001. Planning improvements in natural resources management. Centre for Ecology & Hydrology, Wallingford UK.
	Chapra, S.C., 1997. Surface Water-Quality Modeling. McGraw-Hill, New York.
496	Charniak, E., 1991. Bayesian Networks Without Tears. AI Mag. 12, 14. https://doi.org/10.1145/988164.988169
498	Chen, S.H., Pollino, C.A., 2012. Good practice in Bayesian network modelling. Environ. Model. Softw. 37, 134–145. https://doi.org/10.1016/j.envsoft.2012.03.012
500	de Brouwer, J.H.F., Kraak, M.H.S., Besse-Lototskaya, A.A., Verdonschot, P.F.M., 2019. The significance of
502	https://doi.org/10.1038/s41598-019-38677-6
504	de Vries, J., Kraak, M.H.S., Verdonschot, P.F.M., 2020a. A conceptual model for simulating responses of freshwater macroinvertebrate assemblages to multiple stressors. Ecol. Indic. 117, 106604. https://doi.org/10.1016/j.ecolind.2020.106604
506	de Vries, J., Kraak, M.H.S.S., Verdonschot, R.C.M., Verdonschot, P.F.M.M., 2020b. Species composition drives macroinvertebrate community classification. Ecol. Indic. 119, 106780. https://doi.org/10.1016/i.ecolind.2020.106780
500	dos Reis Oliveira, P.C., van der Geest, H.G., Kraak, M.H.S., Westveer, J.J., Verdonschot, R.C.M.,

- 510 Verdonschot, P.F.M., 2020. Over forty years of lowland stream restoration: Lessons learned? J. Environ. Manage. 264, 110417. https://doi.org/10.1016/j.jenvman.2020.110417
- Elbrecht, V., Beermann, A.J., Goessler, G., Neumann, J., Tollrian, R., Wagner, R., Wlecklik, A., Piggott, J.J., Matthaei, C.D., Leese, F., 2016. Multiple-stressor effects on stream invertebrates: A mesocosm
 experiment manipulating nutrients, fine sediment and flow velocity. Freshw. Biol. 61, 362–375. https://doi.org/10.1111/fwb.12713
- 516 Ellison, A.M., 2004. Bayesian inference in ecology. Ecol. Lett. 7, 509–520. https://doi.org/10.1111/j.1461-0248.2004.00603.x
- Feld, C.K., Birk, S., Bradley, D.C., Hering, D., Kail, J., Marzin, A., Melcher, A., Nemitz, D., Pedersen, M.L., Pletterbauer, F., Pont, D., Verdonschot, P.F.M., Friberg, N., 2011. From Natural to Degraded Rivers and Back Again. A Test of Restoration Ecology Theory and Practice, 1st ed, Advances in Ecological Research. Academic Press. https://doi.org/10.1016/B978-0-12-374794-5.00003-1
- Feld, C.K., Saeedghalati, M., Hering, D., 2020. A framework to diagnose the causes of river ecosystem deterioration using biological symptoms. J. Appl. Ecol. 1–14. https://doi.org/10.1111/1365-2664.13733
- Feld, C.K., Segurado, P., Gutiérrez-Cánovas, C., 2016. Analysing the impact of multiple stressors in
 aquatic biomonitoring data: A 'cookbook' with applications in R. Sci. Total Environ. 573, 1320–
 1339. https://doi.org/10.1016/j.scitotenv.2016.06.243
- 528 Folt, C.L., Chen, Y.C., Moore, M. V., Burnaford, J., 1999. Synergism and Antagonism among Multiple Stressors. Limnol. Oceanogr. 44, 864–877. https://doi.org/10.4319/lo.1999.44.3_part_2.0864
- 530 Friberg, N., 2010. Pressure-response relationships in stream ecology: Introduction and synthesis. Freshw. Biol. 55, 1367–1381. https://doi.org/10.1111/j.1365-2427.2010.02442.x
- Glendell, M., Palarea-Albaladejo, J., Pohle, I., Marrero, S., McCreadie, B., Cameron, G., Stutter, M., 2019.
 Modeling the Ecological Impact of Phosphorus in Catchments with Multiple Environmental
 Stressors. J. Environ. Qual. 48, 1336–1346. https://doi.org/10.2134/jeq2019.05.0195
- Jackson, M.C., Loewen, C.J.G., Vinebrooke, R.D., Chimimba, C.T., 2016. Net effects of multiple stressors in freshwater ecosystems: A meta-analysis. Glob. Chang. Biol. 22, 180–189. https://doi.org/10.1111/gcb.13028
- 538 Janssen, A.B.G., Arhonditsis, G.B., Beusen, A., Bolding, K., Bruce, L., Bruggeman, J., Couture, R.M., Downing, A.S., Alex Elliott, J., Frassl, M.A., Gal, G., Gerla, D.J., Hipsey, M.R., Hu, F., Ives, S.C., Janse,
- J.H., Jeppesen, E., Jöhnk, K.D., Kneis, D., Kong, X., Kuiper, J.J., Lehmann, M.K., Lemmen, C.,
 Özkundakci, D., Petzoldt, T., Rinke, K., Robson, B.J., Sachse, R., Schep, S.A., Schmid, M., Scholten,
 H., Teurlincx, S., Trolle, D., Troost, T.A., Van Dam, A.A., Van Gerven, L.P.A., Weijerman, M., Wells,
- 544 S.A., Mooij, W.M., 2015. Exploring, exploiting and evolving diversity of aquatic ecosystem models: a community perspective. Aquat. Ecol. https://doi.org/10.1007/s10452-015-9544-1
- Kaikkonen, L., Parviainen, T., Rahikainen, M., Uusitalo, L., Lehikoinen, A., 2021. Bayesian Networks in
 Environmental Risk Assessment: A Review. Integr. Environ. Assess. Manag. 17, 62–78. https://doi.org/10.1002/ieam.4332
- 548 Landuyt, D., Broekx, S., D'hondt, R., Engelen, G., Aertsens, J., Goethals, P.L.M., 2013. A review of

550	Bayesian belief networks in ecosystem service modelling. Environ. Model. Softw. 46, 1–11. https://doi.org/10.1016/j.envsoft.2013.03.011
552	Marcot, B.G., 2012. Metrics for evaluating performance and uncertainty of Bayesian network models. Ecol. Modell. 230, 50–62. https://doi.org/10.1016/j.ecolmodel.2012.01.013
554	Marcot, B.G., 2006. Characterizing species at risk I: Modeling rare species under the Northwest Forest Plan. Ecol. Soc. 11. https://doi.org/10.5751/ES-01839-110210
556	Marcot, B.G., Steventon, J.D., Sutherland, G.D., McCann, R.K., 2006. Guidelines for developing and updating Bayesian belief networks applied to ecological modeling and conservation. Can. J. For. Res. 36, 3063–3074. https://doi.org/10.1139/x06-135
558	McCann, R., Marcot, B., Ellis, R., 2006. Bayesian belief networks: applications in ecology and natural resource management. Can. J. For 36, 3035–3062. https://doi.org/10.1139/x06-238
560 562	Mouton, A.M., De Baets, B., Goethals, P.L.M., 2009. Knowledge-based versus data-driven fuzzy habitat suitability models for river management. Environ. Model. Softw. 24, 982–993. https://doi.org/10.1016/j.envsoft.2009.02.005
564 566	 Palmer, M.A., Bernhardt, E.S., Allan, J.D., Lake, P.S., Alexander, G., Brooks, S., Carr, J., Clayton, S., Dahm, C.N., Shah, J.F., Galat, D.L., Loss, S.G., Goodwin, P., Hassett, B., Jenkinson, R., Kondolf, G.M., Lave, R., Meyer, J.L., Donnell, T.K.O., Sudduth, E., 2005. Standards for Ecologically Successful River Restoration. J. Appl. Ecol. 42, 208–217.
568	Palmer, M.A., Menninger, H.L., Bernhardt, E., 2010. River restoration, habitat heterogeneity and biodiversity: A failure of theory or practice? Freshw. Biol. 55, 205–222. https://doi.org/10.1111/j.1365-2427.2009.02372.x
570	Pander, J., Geist, J., 2013. Ecological indicators for stream restoration success. Ecol. Indic. 30, 106–118. https://doi.org/10.1016/j.ecolind.2013.01.039
572 574	Pistocchi, A., 2018. An integrated perspective of multiple stressors in river ecosystems from the catchment to the continental scale, Multiple Stressors in River Ecosystems: Status, Impacts and Prospects for the Future. Elsevier Inc. https://doi.org/10.1016/B978-0-12-811713-2.00020-0
576	Poff, N L., 1997. Landscape Filters and Species Traits : Towards Mechanistic Understanding and Prediction in Stream Ecology. J. North Am. Benthol. Soc. 16, 391–409.
578	Sandin, L., Johnson, R.K., 2004. Local, landscape and regional factors structuring benthic macroinvertebrate assemblages in Swedish streams. Landsc. Ecol. 19, 501–514. https://doi.org/10.1023/B:LAND.0000036116.44231.1c
580	Skeffington, R., Erlandsson, M., Lazar, A., Wade, A.J., Verdonschot, P.F.M., Besse-Lototskaya, A., Moe, J., Acreman, M., Blake, J., Mountford, O., 2014. Adaptive strategies to Mitigate the Impacts of Climate
582	Change on European Freshwater Ecosystems - Deliverable 5.13: Final Report: The REFRESH Models. http://www.refresh.ucl.ac.uk/webfm_send/2380
584	

Tockner, K., Pusch, M., Borchardt, D., Lorang, M.S., 2010. Multiple stressors in coupled river-floodplain

586	ecosystems. Freshw. Biol. 55, 135–151. https://doi.org/10.1111/j.1365-2427.2009.02371.x
588	Trigg, D.J., Walley, W.J., Ormerod, S.J., 2000. A prototype Bayesian belief network for the diagnosis of acidification in Welsh rivers. Dev. Appl. Comput. Tech. to Environ. Stud. 41. https://doi.org/10.2495/ENV000151
590	Uusitalo, L., 2007. Advantages and challenges of Bayesian networks in environmental modelling. Ecol. Modell. 203, 312–318. https://doi.org/10.1016/j.ecolmodel.2006.11.033
592 594	Van der Molen, D.T., Pot, R., Evers, C.H.M., Van Herpen, F.C.J., Van Nieuwerburgh, L.L.J., 2016. Referenties en maatlatten voor natuurlijke watertypen voor de Kaderrichtlijn Water 2015-2021. Rapport 2012-31. Amersfoort.
596	van Echelpoel, W., 2020. Integrating data-driven models and trait-oriented experiments of aquatic macrophytes to support freshwater management. Ghent University.
598	van Puijenbroek, P.J.T.M., Buijse, A.D., Kraak, M.H.S., Verdonschot, P.F.M., 2019. Species and river specific effects of river fragmentation on European anadromous fish species. River Res. Appl. 35, 68–77. https://doi.org/10.1002/rra.3386
600 602	Verberk, W.C.E.P., Durance, I., Vaughan, I.P., Ormerod, S.J., 2016. Field and laboratory studies reveal interacting effects of stream oxygenation and warming on aquatic ectotherms. Glob. Chang. Biol. 22, 1769–1778. https://doi.org/10.1111/gcb.13240
604	Verberk, W.C.E.P., Verdonschot, P.F.M., Haaren, T. van, Maanen, B. Van, 2012. Milieu- en habitatpreferenties van Nederlandse zoetwater- macrofauna: WEW Themanummer 23.
606	Verdonschot, P.F.M., Driessen, J.M.C., Mosterdijk, H.K., Schot, J.A., 1998. The 5-S-Model, an integrated approach for stream rehabilitation. River Restor.
608	Verdonschot, P.F.M., Nijboer, R.C., Janssen, S.N., Van Den Hoorn, M.W., 2000. Ila Ecologische Typologie, on twikkelingsreeksen en waterstreefbeelden: Ecologisch-typologische analyses.
610	Wiens, J.A., 1984. On understanding a non-equilibrium world: myth and reality in community patterns and processes, in: Ecological Communities : Conceptual Issues and the Evidence. Princeton, New Jersey.
612	

Appendix

- 614Table A.1 Node description, type and equation. E: Expert knowledge-based relationship, L: literature-
based, M: relation taken from process-based model. Clip is a Netica function, returning x unless x<min,</th>
- 616 in which case it returns min, or x>max, returning max.

Node name (unit)	Node description	Node	Knowledge	CPT equation
[Abbreviation]		type	base	
Shading (%) [S]	Percentage of the river area which is shaded	Input		NA

Air temperature (°C) [T air]	Mean maximum July Air Temperature	Input		NA
Flow velocity (m/s) [V]	Flow velocity	Input		NA
Stream gradient (m/km) [Sgr]	Stream gradient	Input		NA
Macrophytes (%)	Cover percentage of	Input	E	$M = ((-(\frac{S}{30}) + (\frac{100}{30})) *$
[101]	Macrophytes			$(\operatorname{clip}(0,1,(\frac{\mathrm{TP}}{200}))) * (\operatorname{clip}(0,1,(-2*))) * (\operatorname{clip}(0,1,(-2*)))) * (\operatorname{clip}(0,1,(-2*))) * (\operatorname{clip}($
				$V) + 2)))^{\frac{1}{3}} * 100$
Organic load (mg O2/L) [OL]	Biological Oxygen Demand	Input	E	$OL = \left(\frac{T_{water}}{3}\right) + \left(\frac{A}{50}\right) + \left(\frac{M}{25}\right)$
Max. DO (mg/L)	Maximum Dissolved	Input	L	$DO_Max = 14.6096 - (0.40455 *$
[DO_max]	Oxygen at a given		(Chapra,	T_water) + (0.0080231 *
	temperature		1997)	T_water^2) - (0.0000794339 *
	Actual Dissolved	Innut	1	I_{water} DO = DO = 01 + (2.66 * $V^{0.67}$) +
00 (iiig/ L) [00]	Oxygen Concentration	input	L (Chapra.	$M = M_{Max} - 01 + (2.00 + V) + (M)$
			1997)	$\left(\frac{1}{50}\right) = \left(0.00200 * A\right)$
Temperature (°C)	Water temperature	Input	Μ	$T_w = \ 4.81 \ - \ 0.0716 \ * \ S \ + \ 0.822 \ *$
[T_w]			(Bartholow, 2002)	T _{air}
Algae (µg chl-a/L)	Chlorophyll	Input	E	Algae = $350 * (clip(0,1,(\frac{TP}{600})) *$
[A]	concentrations			$(-(\frac{S}{30}) + (\frac{100}{30})) *$
				$\left(\frac{1}{1+\exp(-0.5*(T_{water}-15))}\right)^{\frac{1}{3}}$
P-tot (µg/L) [TP]	Total phosphorus concentrations	Input		NA
Silt (%) [Si]	Cover percentage of	Input	E	Si = (-(80 * V) + 40) +
	silt			clip(-10,10,(-(15 * Sgr) + 10))
CPOM (%)	Cover percentage for	Input	E	CPOM = (-(200 * V) + 105) +
	Coarse Particulate			cnp(-10,10,(-(15 * Sgr) + 10))
Gravel [G]	Presence of gravel	Input		NA
Wood [W]	Presence of wood	Input		NA

Macroinvertebrates - Substrate [M_sub]	Aggregated suitability score of substrate	Key factor	E	$M_Sub = ((1 - \left 0.5 - \frac{CPOM}{100} \right) * (1 - (Si/100)) * (clip(0,1,W)) * (clip(0,1,G)))^{0.25}$
Macroinvertebrates - Velocity [M_V] Macroinvertebrates - Food Quality [M_FQ]	Aggregated suitability score for flow velocity Aggregated suitability score of food quality	Key factor Key factor	E	$M_V = clip(0,1, (4 * V - 0.2))$ $M_FQ = CPOM/100$
Macroinvertebrates - Dissolved Oxygen [M_DO]	Aggregated suitability score of dissolved oxygen concentration	Key factor	E	$M_D0 = clip(0,1,(D0/7))$
Macroinvertebrates - Temperature [M_T]	Aggregated suitability score of temperature	Key factor	E	$M_{\rm T} = \operatorname{clip}\left(0, 1, \left(-\left(\frac{T_{\rm w}}{10}\right) + 2\right)\right)$
Macroinvertebrates [M]	Aggregated suitability score for macroinvertebrates, taking geometric mean and applying weight to lower values.	Final	Ε	$M = \left(\left(M_T * \frac{1}{1 + \exp(-8*M_T)} \right) * \\ \left(M_{DO} * \frac{1}{1 + \exp(-8*M_{DO})} \right) * \\ \left(M_{FQ} * \frac{1}{1 + \exp(-8*M_{FQ})} \right) * \\ \left(M_V * \frac{1}{1 + \exp(-8*M_V)} \right) * \\ \left(M_{Sub} * \frac{1}{1 + \exp(-8*M_{Sub})} \right) \right)^{0.2}$

Table A.2 Overview of nodes and node states for model version performing best (using equal frequency discretisation)

Node name	State					
	1	2	3	4	5	6
Shading (%)	<16.6	16.6-33.2	33.2-49.8	49.8-66.4	66.4-83	>83
Air temperature (°C)	10-13	13-16.6	16.6-19.9	19.9-23.2	23.2-	>26.5
					26.5	
Flow velocity (m/s)	<0.02	0.02-0.1	0.1-0.15	0.15-0.25	0.25-	>0.33
					0.33	
Macrophytes (%)	<16.6	16.6-33.3	33.3-49.8	49.8-66	66-83	>83
Organic load (mg O2/L)	0-0.7	0.7-1.05	1.05-1.62	1.62-2	2-2.79	>2.79
Max. DO (mg/L)	<8.3	8.3-9.6	9.6-10.9	10.9-12.2	12.2-	>13.5
					13.5	
DO (mg/L)	<6.8	6.8-8	8-9	9-9.88	9.88-	>10.7
					10.7	
Stream temperature (°C)	1.4-9.2	9.2-10.5	10.5-11.5	11.5-12.9	12.9-	>14.3
					14.3	
Algae (µg chl-a/L)	<58	58-117	117-175	175-233	233-292	>292
P-tot (μg/L)	<40.1	40.1-50.1	50.1-75.1	75.1-100	100-180	>180
Silt (%)	<20	20-40	40-60	60-80	>80	
CPOM (%)	<20	20-40	40-60	60-80	>80	
Stream Gradient (m/km)	0-0.5	0.5-1	>1			
Gravel	Present	Absent				
Wood	Present	Absent				
Velocity preference	<0.2	0.2-0.4	0.4-0.6	0.6-0.8	>0.8	
CPOM preference	<0.2	0.2-0.4	0.4-0.6	0.6-0.8	>0.8	
Silt preference	<0.2	0.2-0.4	0.4-0.6	0.6-0.8	>0.8	
Gravel preference	<0.2	0.2-0.4	0.4-0.6	0.6-0.8	>0.8	
Wood preference	<0.2	0.2-0.4	0.4-0.6	0.6-0.8	>0.8	
Macroinvertebrates	<0.2	0.2-0.4	0.4-0.6	0.6-0.8	>0.8	
(Sub)	(Bad)	(Poor)	(Moderate)	(High)	(Good)	
Macroinvertebrates (V)	<0.2	0.2-0.4	0.4-0.6	0.6-0.8	>0.8	
	(Bad)	(Poor)	(Moderate)	(High)	(Good)	
Macroinvertebrates (FQ)	<0.2	0.2-0.4	0.4-0.6	0.6-0.8	>0.8	
	(Bad)	(Poor)	(Moderate)	(High)	(Good)	
Macroinvertebrates (DO)	<0.2	0.2-0.4	0.4-0.6	0.6-0.8	>0.8	
	(Bad)	(Poor)	(Moderate)	(High)	(Good)	
Macroinvertebrates (T)	<0.2	0.2-0.4	0.4-0.6	0.6-0.8	>0.8	
	(Bad)	(Poor)	(Moderate)	(High)	(Good)	

Macroinvertebrates	<0.2	0.2-0.4	0.4-0.6	0.6-0.8	>0.8
	(Bad)	(Poor)	(Moderate)	(High)	(Good)

Table A.3 Number of cases available per node to train model relations. Counted are the number of cases where an observation was available for the node of interest and all of its parent nodes.

Node	Number of cases		
	available for training		
Shading (%)	59		
Air temperature (°C)	0		
Flow velocity (m/s)	722		
Macrophytes (%)	17		
Organic load (mg O2/L)	1		
Max. DO (mg/L)	0		
DO (mg/L)	1		
Stream temperature (°C)	916		
Algae (µg chl-a/L)	2		
P-tot (μg/L)	903		
Silt (%)	289		
CPOM (%)	320		
Stream gradient (m/km)	930		
Gravel	191		
Wood	287		
Velocity preference	25		
CPOM preference	0		
Silt preference	0		
Gravel preference	0		
Wood preference	0		
Macroinvertebrates (Sub)	0		
Macroinvertebrates (V)	0		
Macroinvertebrates (FQ)	0		
Macroinvertebrates (DO)	0		
Macroinvertebrates (T)	0		
Macroinvertebrates	0		



